

DES-5121 Q&As

Specialist - Implementation Engineer - Campus Networking Exam

Pass EMC DES-5121 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.leads4pass.com/des-5121.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Which port security method converts existing dynamically learned MAC addresses on an interface to this mode and no	ot
age out?	

- A. Static
- B. MAC address
- C. Sticky
- D. Dynamic

Correct Answer: D

Reference: https://www.dell.com/support/manuals/us/en/04/networking-s4148f-on/smartfabric-os-user-guide-10-5-1/portsecurity?guid=guid-c27a9d47-ea59-48cc-b19d-90a9f6d52629andlang=en-us

QUESTION 2

A network administrator is planning a PoE budget for their network.

What is the PoE source maximum power budget for a Class 4 end device?

- A. 12.95 watts
- B. 15.4 watts
- C. 34.2 watts
- D. 60 watts

Correct Answer: C

Reference: http://ftp.dell.com/manuals/all-products/esuprt_ser_stor_net/esuprt_networking/esuprt_net_fxd_prt_swtchs/n etworking-n3000-series_User\\'s-Guide10_en-us.pdf page 82

QUESTION 3

A network administrator is setting up several stacks in their network that includes different Dell EMC N-Series models. Which N-Series switch models require mini-SAS stacking cables?

- A. N1100 and N1500
- B. N1500 and N3000
- C. N2000 and N3000
- D. N3000 and N4000

Correct Answer: C



Reference:

https://cdn.cnetcontent.com/syndication/mediaserverredirect/c1ddae5629f69c40c5da9c0d36cb045f/original.pdf

QUESTION 4

What is the recommended maximum number of routers, per area, when using OSPF?

A. 50

B. 100

C. 200 D. 255

Correct Answer: A

QUESTION 5

Refer to the exhibit.

console#show ip access-list broadcast
IP ACL Name: broadcast
Outbound Interface(s): Gi1/0/1
Rule Number: 1000
Actiondeny
Match AllFALSE
Protocol255 (ip)
Source IP Addressany
Destination IP Address255.255.255.255
Destination IP Mask255.255.255.255
ACL Hit Count0
Rule Number: 1010
Actionpermit
Match AllTRUE
ACL Hit Count0



https://www.leads4pass.com/des-5121.html

2024 Latest leads4pass DES-5121 PDF and VCE dumps Download

A network administrator has created an ACL to block broadcast traffic to their server on port Gi1/0/1. Why is the ACL not functioning as desired?

- A. ACL is not applied in the correct direction
- B. ACLs do not support broadcast traffic
- C. Destination address mask is incorrect
- D. Destination IP address is incorrect

Correct Answer: A

DES-5121 VCE Dumps

DES-5121 Practice Test

DES-5121 Braindumps