

# E20-326<sup>Q&As</sup>

Symmetrix Solutions Design Exam for Technology Architects Exam

## Pass EMC E20-326 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/e20-326.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A customer has several internal organizational units with very different requirements for their unique lines of business applications. Which approach provides the most optimal system performance?

- A. Continue to distribute the BCV/Clones/Pools across the front end, back end, engines, and disk.
- B. Segregate the BCV/Clones/Pools across the front end, back end, and engines to optimize each workload on its allocation of system elements.
- C. Continue to distribute the BCV/Clones/Pools across the front end, back end, engines, and disk only if the workloads are highly concurrent.
- D. Segregate the BCV/Clones/Pools across the front end, back end, and engines if the workloads are highly concurrent.

Correct Answer: A

---

**QUESTION 2**

The NAR file on a source CLARiiON array is 12 hours of 600 second intervals. You require a minimum of 20 intervals of complete data.

How many 30-minute trace files will need to be collected from the CLARiiON for a Tier Advisor analysis?

- A. 4
- B. 5
- C. 6
- D. 7

Correct Answer: A

---

**QUESTION 3**

Your customer is using Replication Manager to make local TimeFinder/Clone backups of their Microsoft Exchange 2010 environment. The customer reconfigured the Exchange environment to place the logs on the L:\ drive and mount the database on L:\SG1DB1. They updated the associated Replication Manager replica job to reflect the change. The customer reports that the mount of the database to the backup server now fails.

What do you advise the customer?

- A. Nested mount points are not supported with Replication Manager.
- B. A separate application set must be configured for the database.
- C. Additional clone targets need to be added to the storage pool.
- D. The database replica must be part of the same replica job as the logs.

Correct Answer: A

---

#### QUESTION 4

A customer has implemented a Symmetrix VMAX storage array with FAST VP as a consolidation target for four older storage systems. The storage array is running the current target Enginuity 5875 code. Pool allocation warning levels are set for 65% for the Fibre Channel pool.

If all data migrated to the array is bound to the Fibre Channel pool, how should the configuration of the pool reserve capacity be set?

- A. 1% EFD, 35% FC, 1% SATA
- B. 10% EFD, 10% FC, 10% SATA
- C. 35% EFD, 35% FC, 35% SATA
- D. 90% EFD, 90% FC, 90% SATA

Correct Answer: A

---

#### QUESTION 5

Prior to creating the Symmetrix VMAX architecture for Microsoft SQL, you are given a Perfmon Log view containing data for the database LUN. The file contains read and write IOPS collected over the past week, at 3-minute intervals.

Which method should be used to determine the correct IOPS target for calculating the appropriate number of RAID corrected spindles?

- A. 90th percentile
- B. 75th percentile
- C. Overall Peak
- D. Overall Average

Correct Answer: A

[E20-326 PDF Dumps](#)

[E20-326 Study Guide](#)

[E20-326 Exam Questions](#)