

E20-326^{Q&As}

Symmetrix Solutions Design Exam for Technology Architects Exam

Pass EMC E20-326 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/e20-326.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A colleague implemented cascaded SRDF for a VMAX technology refresh and site relocation activity.

The colleague reports they shutdown the hosts at production Site A and copied all data to the bunker Site

B VMAX. But they are unable to enable SRDF/S between Site B and remote Site C.

What should you advise them?

- A. SRDF/S is not supported on the second leg of a cascaded SRDF implementation.
- B. Enable SRDF/A on the first leg and then enable SRDF/S on the second leg.
- C. Suspend SRDF/S on the first leg and then enable SRDF/S on the second leg.
- D. The Site B devices must be converted to use concurrent SRDF.

Correct Answer: A

QUESTION 2

A customer is using SRDF/S to replicate a Symmetrix VMAX at the production site to the VMAX at the DR site. The sites are connected using a dedicated T1 link and are 38 km apart. What will significantly improve the link service time between the 2 sites?

- A. Upgrade to a faster link.
- B. Decrease the number of RA ports.
- C. Adding cache to both VMAX arrays.
- D. Increase the priority of the high I/O applications on RA ports.

Correct Answer: A

QUESTION 3

A customer is interested in utilizing SRDF/AR to generate a remote copy of an application with an RPO of six hours. In order for you to calculate the bandwidth requirements you will need to run Change Tracker. To which should you set the reset interval length for DeltaMark?

- A. 21600
- B. 86400
- C. 32400
- D. 10800

Correct Answer: D

QUESTION 4

What is the size of a fibre channel frame?

- A. 2112 bytes
- B. 1500 bytes
- C. 9000 bytes
- D. 2148 bytes

Correct Answer: D

QUESTION 5

A customer is implementing a Microsoft Exchange environment on a Symmetrix VMAX. The environment will be deployed on 600 GB FC 15K drives using RAID 1 data protection. The application generates 1350 I/O per second and has a 2:1 read/write ratio.

What is the minimum number of drives recommended to support the application?

- A. 8
- B. 12
- C. 16
- D. 30

Correct Answer: B

[Latest E20-326 Dumps](#)

[E20-326 PDF Dumps](#)

[E20-326 VCE Dumps](#)