

E20-542^{Q&As}

VMAX3 Solutions and Design Specialist Exam for Technology Architects

Pass EMC E20-542 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/e20-542.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A customer wants to know if they will need to enable Dynamic RDF capability for their VMAX3 devices used for SRDF. What information should be provided to the customer?

- A. All VMAX3 thin devices are dynamic RDF capable by default.
- B. Enabling Dynamic RDF requires a bin file change.
- C. Dynamic RDF will need to be manually enabled for each device.
- D. Dynamic RDF will only need to be enabled on the R2 side.

Correct Answer: A

QUESTION 2

What is the best practice guideline for front-end (FA) utilization on a two-engine VMAX3?

- A. 40%
- B. 50%
- C. 60%
- D. 70%

Correct Answer: D

QUESTION 3

The Reserved Capacity for a Storage Resource Pool (SRP) on a VMAX3 has been set to 15%. A TimeFinder SnapVX snapshot has been created for a Storage Group containing 10 devices. An application is actively performing read and write I/Os to these devices. The snapshot is linked to the target in Copy mode. Allocation for the SRP reaches 85%.

What will happen to the copy process?

- A. Copy to the target will halt
- B. Copy to the target will fail
- C. Tracks required for the copy will be allocated from the Reserved Capacity
- D. Copy to the target will continue and complete

Correct Answer: A

QUESTION 4

You are discussing requirements for a proposed VMAX3 solution with a customer. The customer is concerned about the port families that need to be set for the different open system servers in the environment. Which port families are enabled by default?

- A. ACLX, SC3, SPC2
- B. ACLX, SC3, V
- C. ACLX, SPC2, V
- D. SC3, SPC2, V

Correct Answer: A

QUESTION 5

You have been tasked with designing a new VMAX3 array with VMAX Siier. The customer is interested in SRDF/A and TimeFinder SnapVX for some of their applications. Which VMAX Siier parameter allows you to include SRDF/A, SnapVX, and set the desired SLO for these specific applications?

- A. Workload - Table View
- B. Workload - Graph View
- C. Define Constraints - Software Suites
- D. Define Constraints - Local Replication

Correct Answer: A

[Latest E20-542 Dumps](#)

[E20-542 Exam Questions](#)

[E20-542 Braindumps](#)