# E20-616<sup>Q&As</sup>

Symmetrix Installation and Troubleshooting Specialist

### Pass EMC E20-616 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/e20-616.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by EMC Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

😳 365 Days Free Update

Leads4Pass

800,000+ Satisfied Customers



## Leads4Pass

#### **QUESTION 1**

A CE is currently installing a VMAX 40K. Where should the light panel cables of the System Bay be connected?

- A. Engine 4
- B. 1st AC slot
- C. Engine 5
- D. 2nd AC slot
- Correct Answer: A

#### **QUESTION 2**

What is the power level required for VMAX 20K Standard Storage Bay?

- A. 5.3 kVA
- B. 2.5 kVA
- C. 4.9 kVA
- D. 3.5 kVA
- Correct Answer: A

#### **QUESTION 3**

Which SRDF/A feature prevents cache overflow on either the R1 or R2 devices?

- A. Write Pacing
- B. Transmit Idle
- C. SRDF Compression
- D. Delta Set Extension
- Correct Answer: A

#### **QUESTION 4**

What is the vault hyper size in GB for configuring a new VMAX 40K?

- A. 9
- B. 5

### Leads4Pass

C. 4.5

D. 0.5

Correct Answer: A

#### **QUESTION 5**

Refer to the exhibit.

Fibre Loops				DAEs						
ES	DA/DI	IOM	Port	0	1	2	3	4	5	6
1	1/2	0	AO	S						
			A1	S	V	V				
			BO	S						
			B1	V	V	٧				
		1	CO	S						
			C1	V	V	V				
	enseriertes		DO	S						
			D1	V	V	V				

What does \\'V\\' represent under the DAE Map Window of SymmWin?

- A. 25 disk drive DAE
- B. Surrogate
- C. 15 disk drive DAE
- D. Volume Set Addressing

Correct Answer: A

E20-616 PDF Dumps

E20-616 Exam Questions

E20-616 Braindumps