

E20-616^{Q&As}

Symmetrix Installation and Troubleshooting Specialist

Pass EMC E20-616 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/e20-616.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A director replacement is required on VMAX 20K. The customer asks what the impact will be on the front-end ports of the director being replaced. What should your response be?

- A. The front-end I/O modules will go offline.
- B. The front-end I/O modules will use a redundant Virtual Matrix.
- C. The front-end I/O modules will use redundant SIB.
- D. The front-end I/O modules will remain online.

Correct Answer: A

QUESTION 2

What is an advantage of using the Hosts tab when creating an open system configuration with SymmWin?

- A. Volume addressing is easier in the Vols Map
- B. Automatically copies sets director flags on the ports
- C. It is designed to add an unknown host to the configuration
- D. The "rule of 17" is automatically invoked when selecting port pairs

Correct Answer: A

QUESTION 3

Refer to the exhibit.

Init DirMap DirEdit Hosts DAE Disks VolReq VolMap VolEdit VolDist Algo																				
FDA-Link		FA-Link																		
ID	dirs	Common SN (C)	Disable Queue	Enable Sunapee	Enable Siemens	Sequent Host	Avoid Reset Broadcast	SCSI 3 Interface	SCSI Primary	OS 2007	Enable Volume	Non Participate	Enable point	Unique Worldwide	Enable FibrePath	Open VMS	Enable Auto	FA AS400	link speed	Port
- 07a		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	PP	UwN	VCM	ovms	ean	as4	2G	A
		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	PP	UwN	vcm	ovms	ean	as4	2G	B
- 07b		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	pp	UwN	vcm	ovms	EAN	as4	1G	A
		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	pp	UwN	vcm	ovms	EAN	as4	1G	B
- 07c		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	PP	UwN	VCM	ovms	ean	as4	4G	A
		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	PP	UwN	vcm	ovms	ean	as4	4G	B
- 07d		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	PP	UwN	vcm	ovms	ean	as4	1G	A
		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	PP	UwN	vcm	ovms	ean	as4	1G	B
- 08a		C	d	scl	s	seq	arb	sc3	spc2	os2007	y	np	PP	UwN	vcm	ovms	ean	as4	1G	B

When would you use the '\\EAN\\' bit setting in SymmWin?

- A. If the SAN speed is unknown
- B. To enable SAN topology
- C. To Enable iSCSI negotiation
- D. If IP network speed will be negotiated

Correct Answer: A

QUESTION 4

Which disk types can be used in a Symmetrix VMAX?

- A. SATA II, Fibre Channel, SAS and Enterprise Flash Drive (EFD)
- B. SAS, SCSI, Fibre Channel, and Enterprise Flash Drive (EFD)
- C. SCSI, SATA II, Fibre Channel, and Enterprise Flash Drive (EFD)
- D. SAS, Fibre Channel, SCSI and SATA II (SSD)

Correct Answer: C

QUESTION 5

What is a SymmWin Best Practice when configuring disk drives?

- A. Smaller drives perform better.
- B. Go deep then wide when adding drives.
- C. Protection type is irrelevant.
- D. Use Raid 5 instead of Raid 6 when data availability is secondary.

Correct Answer: A

[Latest E20-616 Dumps](#)

[E20-616 PDF Dumps](#)

[E20-616 Brindumps](#)