

## H12-211<sup>Q&As</sup>

HCIA-Routing & Switching V2.2

**Pass Huawei H12-211 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/h12-211.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

reset saved-configuration

Warning:The action will delete the save configuration in the device.The configuration will be erased to

reconfigure.Continue?[Y/N]:

The administrator performs the following configuration on the AR2200. The following description about the configuration information is correct ().

- A. If the user wants to clear the saved configuration file, he should choose Y.
- B. The configuration file will be retained when the device starts up.
- C. If the user wants to clear the saved configuration file, he should choose N
- D. The saved configuration file will be replaced by the running configuration file.

Correct Answer: A

---

## QUESTION 2

After the keepalive function is enabled for a GRE tunnel, the local end of the GRE tunnel sends a keepalive packet to the remote end every 10s.

- A. True
- B. False

Correct Answer: B

---

## QUESTION 3

When RIPv1 is enabled on the Huawei router, the interface that is advertised to the RIP receives the RIPv1 broadcast packet, the RIPv2 broadcast packet, and the multicast packet by default.

- A. Yes
- B. Wrong

Correct Answer: A

---

## QUESTION 4

The following shows the command output on a router.

Which of the following statements are true?

display startup MainBoard: Startup system software: flash:/AR2220E-V200R007C00SPC600.cc Next startup system software: flash:/AR2220E-V200R007C00SPC600.cc Backup system software for next startup: null Startup saved-configuration file: flash:/vrpcfg.zip Next startup saved-configuration file: flash:/backup.zip Startup license file: null Next startup license file: null Startup patch package: null Next startup patch package: null Startup voice-files: null Next startup voice-files: null

- A. The current VRP version file is the same as the VRP file for next startup.
- B. The current VRP version file is different from the VRP file for next startup.
- C. The current configuration file is the same as the configuration file for next startup.
- D. The current configuration file is different from the configuration file for next startup.

Correct Answer: CD

---

#### QUESTION 5

```
[RTA]aaa
[RTA-aaa]domain huawei
[RTA-aaa-domain-huawei]authentication-scheme au1
[RTA-aaa-domain-huawei]authentication-scheme au2
```

Refer to the configuration output. RTA has been configured using AAA as shown, and associated with the "huawei" domain. For users in the huawei domain, which authentication-scheme will be used?

- A. au1
- B. au2
- C. au1 will be used. When au1 is deleted, users will use au2
- D. au2 will be used. When au2 is deleted, users will use au1

Correct Answer: B

[Latest H12-211 Dumps](#)

[H12-211 Study Guide](#)

[H12-211 Exam Questions](#)