

H12-261^{Q&As}

HCIE-Routing & Switching (Written) V3.0

Pass Huawei H12-261 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/h12-261.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

In judging the old and new LSA, age, , the serial number parameter and the parameter are used. The following two parameters are correct.

- A. When the router receives a LSA age 360s, the LSA says that this is not available.
- B. The serial number and parameters can be judged. The old and new routers are better than the age LSA and sequence.
- C. When the router receives two of the same serial numbers and the same LSA, , , the check is smaller and better
- D. If the serial number reaches the bundle LSA 0x7FFF age 3600s lsa value, the current router is advertised as

Correct Answer: C

QUESTION 2

A network administrator plans to migrate IGMPv2 to IGMPv3 on the multicast network. What advantages does IGMPv3 have over IGMPv2?

- A. IGMPv3 deletes suppression of IGMPv3 Membership Report messages
- B. IGMPv3 deletes the function of matching all sources through wildcard belong to specific multicast group
- C. IGMPv3 enables a host to join a specified multicast group that excludes a specified multicast source
- D. IGMPv3 adds Request-to-Send and Clear-to-Send messages between source and local IGMP queries
- E. IGMPv3 enables a host to join a specified multicast group that includes a specified multicast source

Correct Answer: E

QUESTION 3

In the context of MPLS-BGP-VPN BGP LDP MPLS ring, if only the label is distributed and distributed, then the label layer label of the document is up to two.

- A. True
- B. False

Correct Answer: B

QUESTION 4

What is the correct description of the reflector? Multiple BGP () selection

- A. The route reflector can advertise all IBGP client non-client neighbors from the learned route.

- B. In the absence of a route reflector, the relationship needs to be fully inter-IBGP neighbors, and the introduction of route reflectors can reduce the requirement for full inter-connection.
- C. The route reflector can advertise all non-client clients from the learned routes.
- D. The route reflector can advertise other client client non-client from a learned route.

Correct Answer: BCD

QUESTION 5

If PIM-SM is enabled on a multicast network, an RP needs to be configured. The RP can be configured the following statements regarding RP configuration is true?

- A. No BSR needs to be configured when a dynamic RP is configured.
- B. When a static RP is configured, you need to configure a BSR that advertises RP information.
- C. The BSR needs to be configured as the RP backup when a dynamic RP is configured.
- D. RP information needs to be specified on all PIM routers when a static RP is configured-

Correct Answer: C

[H12-261 VCE Dumps](#)

[H12-261 Practice Test](#)

[H12-261 Exam Questions](#)