

H12-831^{Q&As}

HCIP-Datacom-Advanced Routing & Switching Technology V1.0

Pass Huawei H12-831 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/h12-831.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

To speed up the detection of link failures in an IS-IS network, you can associate IS-IS with BFD.

- A. True
- B. False

Correct Answer: A

QUESTION 2

A campus deploys both IPv4 and IPv6 networks for service testing, and runs IS-IS to realize network interconnection. The IS-IS routing protocol has good scalability and is widely used in the existing network. Which of the following statements is true about IS-IS scalability?

- A. IS-IS uses TLV structure to build the message so that IS-IS has more flexibility, flexibility and scalability
- B. For IS-IS, in terms of adding new features, only adding new TLV is just
- C. IS-IS supports IPv6 to add TLV to carry IPv6 address information
- D. No. IPv6 is supported by IS-IS to support IPv6 and an added TLV

Correct Answer: ABC

QUESTION 3

The correct description for the configuration on this switch is: [Huawei]dhcp enable [Huawei]interface Vlanif 100 [Huawei-Vlanif 100]dhcp select relay

```
[Huawei]dhcp enable
[Huawei]interface Vlanif 100 [Huawei-Vlanif 100]dhcp select relay
```

- A. You just need to create DHCP server and DHCP relay must be enabled globally
- B. For VLAN 100 interface designation DHCP server group is dhcp group
- C. First you need to create DHCP server group and add to server group DHCP server
- D. VLAN 100 interface will receive the DHCP message, sent to the outside through the relay DHCP server

Correct Answer: ABCD

QUESTION 4

As shown in the figure, the MP_BGP neighbor relationship is established between PE1 and PE2 through the LoopbackO interface. After the configuration is complete, it is found that CE1 and CE2 cannot learn routes from each other. Which of the following options will cause this problem.



- A. PE1 or PE2 not present BGP-VPNv4 Enabling neighbors in unicast address family view
- B. PE1 or PE2? fVPN Instance parameter configuration error
- C. PE1 and PE2 between LSPTunnel not established
- D. PE1 or PE2 with each other CE Misconfigured routing protocol between

Correct Answer: ABCD

QUESTION 5

In addition to virtual connections, what type of IPv6 address is the source IPv6 address of OSPFv3's Hello text?

- A. IPv6 anycast address
- B. unique local address
- C. Global Unicast Address
- D. link-local address

Correct Answer: D

[H12-831 PDF Dumps](#)

[H12-831 VCE Dumps](#)

[H12-831 Exam Questions](#)