

# HCE-3700<sup>Q&As</sup>

Hitachi Vantara Certified Expert - Performance architect

## Pass Hitachi HCE-3700 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hce-3700.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

A VSP G800 HDT pool contains FMDs, NL-SAS drives, external storage with 15K 600 GB SAS drives, and external storage with 10K 900 GB SAS drives.

Which tier level contains the NL-SAS drives in this configuration?

- A. 1
- B. 2
- C. 3
- D. 4

Correct Answer: A

---

**QUESTION 2**

Relocation cycles are regulatory failing to complete in an HDT implementation where the customer is also reporting lower than expected performance.

What should be done in this scenario?

- A. Change to Continuous mode and increase the monitor period cycle time.
- B. Change to Period mode and increase the monitor period cycle time.
- C. Change to Period mode and reduce the monitor period cycle time.
- D. Change to High-Performance mode and reduce the monitor period cycle time.

Correct Answer: B

---

**QUESTION 3**

You are planning for a performance upgrade for a transaction application.

Which three metrics are necessary to determine the required back-end storage configuration in this scenario? (Choose three.)

- A. cache read hit ratio
- B. read/write ratio
- C. transfer rates
- D. queue depth
- E. IOPS

Correct Answer: ABE

---

#### QUESTION 4

You are troubleshooting a potential marginal link in a SAN fabric that you believe is causing a performance problem.

To troubleshoot this problem, which two actions will allow you to view the detailed port statistics? (Choose two.)

- A. Use the vendor's GUI.
- B. Use the appropriate host command(s).
- C. Use the appropriate switch command(s).
- D. Use SVP Performance Monitor.

Correct Answer: AC

---

#### QUESTION 5

A user reports fluctuating LUN response times every day between 8:00 AM and 9:00 AM as users arrive and log in.

How do you identify this condition using Hitachi Tuning Manager?

- A. View LUN response times and RAID group utilization (% busy) averaged over the 60 minutes.
- B. View the random write counts every minute.
- C. View LUN response times and RAID group utilization (% busy) every minute.
- D. View LUN response times and correlate against the Cache Write Pending level every 15 minutes.

Correct Answer: A

[Latest HCE-3700 Dumps](#)

[HCE-3700 VCE Dumps](#)

[HCE-3700 Braindumps](#)