HP2-K39^{Q&As}

Support and Service HP StoreOnce Multinode Solutions

Pass HP HP2-K39 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.lead4pass.com/HP2-K39.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

365 Days Free Update

800,000+ Satisfied Customers

QUESTION 1

How do you perform a tailback of a service set running on node two after you fix hardware issues on an HP StoreOnce Multi-node system?

A. Execute ^hardware fallback node2.

B. Perform a regular shutdown of both nodes.

C. Restart Service Set one on node two.

D. Reboot the IBRIXfile system.

Correct Answer: C

QUESTION 2

You are using Catalyst and duplication to size an OST solution for a Symantec NetBackup customer. Which statement is true regarding HP StoreOnce 6500 Backup system licensing options?

A. Only the source system has to be licensed.

B. The initial couplet on the target side has to be licensed.

C. The source and target systems have to be licensed.

D. Only the target system has to be licensed.

Correct Answer: C

QUESTION 3

Your customer implements some changes within the existing TCP/IP environment. The changes affect the existing HP StoreOnce Multi-node environment and the current backup infrastructure. How can you apply the new network configuration on the HP StoreOnce 6500 Backup system?

A. Replace the old configuration with the correct TCP/IP information using the CLI parameter Pnet set change, and reboot the cluster nodes.

B. Configure an alternate network template, and then re-apply the template with all the modified network settings.

C. Access the console of the first node, change all the parameters, and sync the nodes within the cluster.

D. Modify the configuration using the GUI (Device configuration - Network), and apply the configuration.

Correct Answer: A

QUESTION 4

You need to update the hardware firmware on your customer\\'s Multi-node HP StoreOnce Backup system. Which task needs to be performed prior to updating the firmware?

A. Failover needs to be disabled.

B. Network bonding modes need to be disabled.

C. The hardware status report must be run.

D. Service set two needs to be taken offline.

Correct Answer: C

QUESTION 5

What is the HP vision for Catalyst replication technologies and concepts for the near future? (Select two.)

A. The regional HP StoreOnce Backup system can act as a DR capability for small branch offices.

B. With all SSD HP StoreOnce Backup systems, data replication will require 10Gb WAN networking,

C. The HP StoreOnce Backup system will rely more on SAN controller based replication,

D. Replication will become localized to ensure performance and restore SLAs.

E. Data from small branch offices can be replicated to small regional offices.

Correct Answer: BC

[HP2-K39 VCE Dumps](#)   [HP2-K39 Practice Test](#)   [HP2-K39 Braindumps](#)

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: