

HP2-T16^{Q&As}

Industry Standard Architecture and Technology

Pass HP HP2-T16 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hp2-t16.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

In the GFS backup tape rotation plan, which type of backup is the Father?

- A. copy
- B. normal
- C. differential
- D. incremental

Correct Answer: B

```
{\rtf1\ansi\ansicpg936\deff0\deflang1033\deflangfe2052{\fonttbl{\f0\fnil\fcharset0 MS Shell Dlg 2;}}\viewkind4\uc1\pard\lang2052\fs17 Industry Standard Architecture - Student Guide 2 - Page 302:\par Grandfather-Father-Son tape rotation \par The system administrator typically performs a full backup every Monday (father) and incremental backups on Tuesdays, Wednesdays, and Thursdays (sons). The administrator performs another full backup at the end of the week (father) and another at the end of the month (grandfather).\par }
```

QUESTION 2

You are asked to update the firmware of the backplane of an external disk enclosure to the latest versions. The disk enclosure is connected to a RAID adapter on your server. You have updated the firmware successfully and rebooted to complete the setup. The disk enclosure does not start after rebooting. What can be done to resolve the problem? (Select three)

- A. Roll back to the old firmware revision.
- B. Ensure that the disk enclosure is connected to a working AC source.
- C. Ensure that the power source and power supplies are working properly.
- D. Replace the disk enclosure.
- E. Remove the AC power cords from both enclosure power supplies and reinsert them.

Correct Answer: ADE

QUESTION 3

Which statements are true about AMD 2P or 4P system architecture? (Select three)

- A. Requests for memory access are handled by the Northbridge ASIC.
- B. Memory must be installed in banks corresponding to the installed processors.
- C. Each processor has its own memory controller
- D. The maximum amount of memory can be installed, regardless of the number of installed processors.

E. Requests for memory access are handle directly by the corresponding processor and relayed through the HyperTransport link.

F. Communications between CPU and memory is handle through the QuickPath Interconnect.

Correct Answer: BCE

QUESTION 4

What are recommended procedures to ensure backup media is securely stored? (Select two)

- A. Place the backup media in a fire-proof safe.
- B. Ensure the switch on backup tapes is set to lock.
- C. Store a copy of all backup media in a locked server rack.
- D. Have a bonded third-party firm store backup media at a secure remote facility
- E. Take a copy of all backup media home.

Correct Answer: AD

```
{\rtf1\ansi\ansicpg936\deff0\deflang1033\deflangfe2052{\fonttbl{\f0\fnil\fcharset0 MS Shell Dlg 2;}}\viewkind4\uc1\pard\lang2052\fs17 Industry Standard Architecture - Student Guide 2 - Page 203\par Ensuring security of backup media\par The following are some of the methods used to secure backup media:\par Lock the media in an office.\par Lock the media in a cabinet with strict key control.\par Place the media in a safe or in a fire-safe.\par Engage a bonded third-party firm to store the media in their secure facility.\par }
```

QUESTION 5

All the RAID sets in a server system are no longer accessible. Which step should be taken first to troubleshoot this problem?

- A. Replace the array controller.
- B. Pull all the disks except one in orer to get a lease on working.
- C. Start the system with the OS installation CD to repartition the hard drives.
- D. Use the array controller diagnostics utility to verify the array status.

Correct Answer: D

[Latest HP2-T16 Dumps](#)

[HP2-T16 Exam Questions](#)

[HP2-T16 Braindumps](#)