

## HP2-Z33<sup>Q&As</sup>

HP Unified Wired-Wireless Networks and BYOD

### Pass HP HP2-Z33 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hp2-z33.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

In 802.11n, what does fat channel intolerance indicate?

- A. Clients hearing this information must transmit in the secondary channel only.
- B. Both the clients and access points hearing this information must no longer aggregate MPDU frames.
- C. Access points hearing this information must use the default 40 MHz channel bandwidth.
- D. Access points hearing this information must prohibit the use of 40 MHz channels.

Correct Answer: D

Reference: <http://forums.anandtech.com/showthread.php?t=249626> (last post on the page) Fat Channel Intolerant Communicates to surrounding networks that this WiFi adapter is not tolerant of 40MHz channels in the 2.4GHz band.

---

**QUESTION 2**

A customer has an HP BYOD solution based on an HP 830 Unified Wired-Wireless Controller and HP 425 Access Points (APs). To ease the controller adoption of the APs, a VLAN is set up on the corporate LAN. How should this VLAN be configured?

- A. Set the VLAN on the switches between the APs and Comware L3 switch
- B. Set the VLAN as VLAN 1
- C. Set the VLAN on the switches between the APs and 830 wireless controller
- D. Set the VLAN on the switches between the APs and the 830 switch

Correct Answer: A

---

**QUESTION 3**

A network administrator sets up the DHCP relay on an HP Comware Layer 3 device that forwards IP traffic between the VLANs associated with the wireless SSID with these commands.

```
interface Vlan-interface 100
description internet access
ip address 10.1.100.1 255.255.255.0
dhcp select relay
dhcp relay server-select 0
```

What must the administrator configure prior to enabling the DHCP relay to the DHCP server on 10.0.0.200 in the interface vlan-interface 100?

- ```
A  Interface vlan 100
    dhcp relay server-group 0 ip 10.0.0.200

B  system-view
    dhcp enable
    dhcp relay server-group 0 ip 10.0.0.200

C  system-view
    dhcp select relay
    dhcp relay server-group 0 ip 10.0.0.200

D  system-view
    dhcp relay server-group 0 ip 10.0.0.200
```

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: B

---

#### QUESTION 4

Which statement is correct about security on a wireless network?

- A. 802.1X with EAP-TLS mode provides encryption without authentication.
- B. In MAC authentication, the MAC address can be spoofed.
- C. 802.1X with PEAP MSCHAPV2 provides authentication without encryption.
- D. MAC authentication provides encryption.

Correct Answer: B

---

#### QUESTION 5

A company plans to deploy an HP MSM wireless network. The company currently has a RADIUS server that is used to control employee access to the company's Intranet from wired clients. They want to use the same RADIUS server to control employee's access from wireless clients.

The company also wants to allow guests to connect to the wireless network. They want to allow the guests to reach the

Internet, but they want to make sure that guests cannot reach the company's Intranet.

Based on these requirements, which traffic optimization scheme should be implemented?

- A. Deploy distributed forwarding for employees and distributed forwarding with centralized authentication for guests.
- B. Deploy distributed forwarding for employees and centralized access control for guests.
- C. Deploy centralized access control for employees and distributed forwarding with centralized authentication for guests.
- D. Deploy centralized access control for employees and distributed forwarding for guests.

Correct Answer: C

[Latest HP2-Z33 Dumps](#)

[HP2-Z33 PDF Dumps](#)

[HP2-Z33 Study Guide](#)