

HPE0-V14^{Q&As}

Building HPE Hybrid IT Solutions

Pass HP HPE0-V14 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hpe0-v14.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A customer requires a management solution that will provide email notifications if hardware errors occur on their servers. Which management solution provides this functionality?

- A. UEFI System Configuration
- B. iLO Advanced Edition
- C. HPE SUM
- D. HPE SUT

Correct Answer: B

https://support.hpe.com/hpesc/public/docDisplay?docLocale=en_US&docId=emr_na-a00026111en_us#N11E72 iLO AlertMail enables user to configure iLO to send alert conditions detected independently of the host operating system to one or more email addresses. iLO AlertMail messages include major host system events that appear in the IML. For example, if a fan failure occurs, an event is recorded in the IML and an email message with the details is sent to the configured email addresses.

Reference: https://support.hpe.com/hpesc/public/docDisplay?docLocale=en_US&docId=emr_na-a00026111en_us

QUESTION 2

Refer to the exhibit.

```
admin> cfgshow

Defined configuration:
  cfg:      zone_cfg_1
           nimble_esx_1_zone
zone:      nimble_esx_1_zone
           ESX1; NIMBLE1A
alias:     ESX1 51:40:2e:c0:11:0b:a4:c0
alias:     NIMBLE1A
           56:c9:ce:90:20:50:68:01

Effective configuration:
  cfg:      zone_cfg_1
zone:      nimble_esx_1_zone
           51:40:2e:c0:11:0b:a4:c0
           56:c9:ce:90:20:50:68:01
```

When performing a code upgrade on an HPE Nimble array, you noticed a connection failure on ESX1. Refer to the exhibit showing the complete zoning configuration of one of the HPE SN3000B switches. What should you do to ensure storage access is not interrupted when doing the next update?

- A. Create and ISL between the two HPE SN3000B switches.
- B. Create a new zone for ESX1 and the second storage controller.
- C. Change the timeout values on the SN3000B switch.
- D. Configure the same zone on a second HPE SN3000B.

Correct Answer: B

QUESTION 3

A customer needs a low cost block storage array for targeted workloads. The array needs to provide automated tiering, thin provisioning, and snapshot capabilities. Which HPE storage solution meets the customer requirements?

- A. HPE MSA
- B. HPE D3000
- C. HPE Nimble
- D. HPE StoreEasy

Correct Answer: A

Reference: <https://h20195.www2.hpe.com/v2/getpdf.aspx/A00015961ENW.pdf>

QUESTION 4

A customer has a HPE OneView environment and has added all their HPE ProLiant servers and enclosures.

Which benefits does a customer gain by configuring Remote Support on their environment? (Choose two.)

- A. Support case resolutions are automatically generated for them based on real-time analyses
- B. HPE is given remote access rights to registered devices for quick and accurate problem resolution
- C. HPE Proactive Care is enabled and cases are created automatically in the event of hardware failures
- D. Proactive Scan reports and firmware/software analysis reports can be provided from collected data
- E. Real-time performance analytics result in failure predictions and online self-healing

Correct Answer: CD

QUESTION 5

DRAG DROP

A customer considers a new HPE ProLiant DL380 Gen10 as a hardware platform for their application and requires maximum physical security.

For each security-related server components, identify whether it needs to be ordered separately, or whether it is included as part of the server solution.

Select and Place:

Answer Area	
Included with the server	Chassis Intrusion detection
Needs to be ordered separately	Certified TPM 2.0
	Silicon Root of Trust
	Digitally signed firmware

Correct Answer:

Answer Area	
Included with the server	Chassis Intrusion detection
Needs to be ordered separately	Certified TPM 2.0
Needs to be ordered separately	Silicon Root of Trust
Included with the server	Digitally signed firmware