

HPE6-A67^{Q&As}

Aruba Certified ClearPass Associate 6.7

Pass HP HPE6-A67 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hpe6-a67.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which options support DHCP profiling for devices in a network? (Choose two.)

- A. configuring ClearPass as a DHCP relay for the client
- B. enabling the DHCP server to profile endpoints and forward meta-data to ClearPass
- C. enabling DHCP relay on our network access devices so DHCP requests are forwarded to ClearPass
- D. enabling the DHCP server to forward DHCP traffic to ClearPass
- E. DHCP profiling is enabled on ClearPass by default; configuration of the network access devices is not necessary

Correct Answer: AC

QUESTION 2

When Active Directory is added as an authentication source, what should the format be for the Active Directory bin DN?

- A. admin.domain.com
- B. domain.com\admin
- C. domain.com
- D. admin@domain.com
- E. admin\domain.com

Correct Answer: D

QUESTION 3

What happens when a client successfully authenticates but does not match any Enforcement Policy rules?

- A. no role is applied to the device
- B. logon profile is applied to the device
- C. default Enforcement profile is applied
- D. guest rule is applied to the device
- E. default rule is applied to the device

Correct Answer: C

QUESTION 4

Which agents are valid Posture agents used by the ClearPass Policy Manager? (Select three.)

- A. OnGuard persistent agent
- B. Microsoft AD
- C. OnGuard dissolvable agent
- D. Cisco Trust Agent
- E. Microsoft NAP

Correct Answer: ACE

QUESTION 5

When enforcement action is used in ClearPass to bounce a client?

- A. Webpage redirect
- B. ACL
- C. VLAN attribute
- D. RADIUS VSA
- E. RADIUS CoA

Correct Answer: E

In the Profiler tab, change the RADIUS CoA Action to "[Cisco - Bounce-Host-Port]". Make sure your switch is configured for this.

Reference: <http://community.arubanetworks.com/t5/Security/MAC-Auth-Service-for-AP-s-Printers-Etc/td-p/243252>

[HPE6-A67 Practice Test](#)

[HPE6-A67 Exam Questions](#)

[HPE6-A67 Braindumps](#)