

# HPE6-A70<sup>Q&As</sup>

Aruba Certified Mobility Associate Exam

**Pass HP HPE6-A70 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hpe6-a70.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

What is one difference between how administrators can use the Mobility Master (MM) Interface as compared to the AirWave Management Platform?

- A. AirWave shows trends for the past several minutes, while MM shows historical data.
- B. MM shows trends for the past several minutes, while AirWave shows historical data.
- C. AirWave shows the current signal level for the client connection, while MM does not show RF statistics.
- D. MM shows user and role information associated with clients, while AirWave does not.

Correct Answer: B

---

## QUESTION 2

A WLAN in an Aruba Mobility Master (MM)-based solution uses WPA2-Enterprise security. This WLAN currently authenticates users to Active Directory (AD), and users log in with their Windows domain credentials. Network administrators now want to authenticate the Windows clients as well, based on the client Computer Names. What should the administrators do on MM to achieve this goal?

- A. Set up Machine Authentication on the WLAN.
- B. Set up Mac Authentication on the WLAN.
- C. Bind individual Mobility Controllers (MCs) to AD at the device level.
- D. Import the computer names from AD to the MM internal database.

Correct Answer: A

---

## QUESTION 3

Which pre-defined role allows DHCP, DNS, and internal captive portal redirection for a guest WLAN?

- A. exam\_guest-guest-logon
- B. authorized
- C. guest-logon
- D. guest

Correct Answer: C

---

## QUESTION 4

A network administrator configures this policy:

```
ip access-list session Guest
  user any svc-dhcp permit
  user any network 10.0.0.0 255.0.0.0 deny
  user any any permit
```

Users to which this policy applies are unable to receive IP addresses with DHCP. How should the administrator fix the issue?

- A. Change user to any in the user any svc-dhcp permit rule.
- B. Move the user any svc-dhcp permit rule to the bottom of the list.
- C. Remove the deny rule from the policy.
- D. Use the correct service alias in the user any svc-dhcp permit rule.

Correct Answer: D

---

#### QUESTION 5

A company has an Aruba Mobility Master (MM)-based solution with a WLAN that assigns users to VLANs 10-19. The company wants the Aruba solution to act at Layer 3 to route wireless user traffic. What must network administrators configure to permit the solution to forward traffic correctly?

- A. VLAN 10-19 interfaces and proper IP settings on the MM nodes
- B. trunk ports that support VLANs 10-19 on the managed Mobility Controllers (MCs)
- C. VLAN 10-19 interfaces on the Mobility Controllers (MCs) as the default gateway for wireless users
- D. trunk ports that support VLANs 10-19 on the MM nodes

Correct Answer: C

[Latest HPE6-A70 Dumps](#)

[HPE6-A70 VCE Dumps](#)

[HPE6-A70 Exam Questions](#)