

HPE6-A70^{Q&As}

Aruba Certified Mobility Associate Exam

Pass HP HPE6-A70 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hpe6-a70.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A company deploys a wireless network in a typical office environment with many surfaces where the signal can bounce. Which 802.11 technology uses the characteristics of this environment to increase wireless speeds?

- A. Channel bonding
- B. Multiple Input Multiple Output (MIMO)
- C. Transmit Power Control (TPC)
- D. QAM modulation

Correct Answer: B

QUESTION 2

A company has an Aruba solution with a guest WLAN named exam_guest. A network administrator creates the guest WLAN with the wizard and does not change any of the default roles. The authentication server does not send particular role assignments for authorized users. The company wants to deny guest access to specific IP ranges after the guests authenticate. For which role should the administrator create the rule to deny this traffic?

- A. exam_guest-guest-logon
- B. authorized
- C. guest-logon
- D. guest

Correct Answer: D

QUESTION 3

Refer to the exhibits. Exhibit 1

Roles>users1

GLOBAL RULES



RULES FOR THIS ROLE ONLY

- ◇ permit all from source any to alias network1
- ◇ deny all from source any to network
172.16.0.0/255.255.0.0
- ◇ permit all from source user to any destinations

Exhibit 2

Roles Policies Applications

Roles > users2

[Show Advanced View](#)**GLOBAL RULES**

**RULES FOR THIS ROLE ONLY**

- ◇ permit all from source user to network 10.1.1.0/255.255.255.0
- ◇ deny all from source user to network 10.1.2.0/255.255.255.0
- ◇ permit all from source user to network 10.1.0.0/255.255.0.0

A company has an Aruba solution. Client 1 is assigned to the users1 role, and client 2 is assigned to the users2 role. The exhibits show current firewall rules for those roles. The network1 alias used to be 10.1.1.0/24, but the network administrator now changes the network1 alias to 172.16.1.0/24. Client 1 and Client 2 both send a packet destined to 172.16.1.10. How does the firewall handle these packets?

- A. It permits the packet from Client 1 and denies the packet from Client 2.
- B. It permits both packets.
- C. It denies the packet from Client 1 and permits the packet from Client 2.
- D. It denies both packets.

Correct Answer: A

QUESTION 4

An Aruba Mobility Master (MM)-based solution has a WLAN that uses WPA2-Enterprise security. A test login on a wireless client fails.

How can a network administrator determine whether the RADIUS server rejected the credentials or another issue occurred?

- A. View Technical Support information for the MM.

- B. Ping the IP address configured as the RADIUS server.
- C. Use the MM AAA Server Test Diagnostic tool.
- D. Use the tools in the MM Dashboard > Security window.

Correct Answer: C

QUESTION 5

Which IEEE standard provides the highest transmission rates in the 2.4GHz frequency band?

- A. 802.11a
- B. 802.11ac
- C. 802.11g
- D. 802.11n

Correct Answer: D

[HPE6-A70 Practice Test](#)

[HPE6-A70 Study Guide](#)

[HPE6-A70 Exam Questions](#)