

HPE6-A71^{Q&As}

Aruba Certified Mobility Professional Exam

Pass HP HPE6-A71 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hpe6-a71.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

An administrator implements a ClearPass solution to authenticate Aruba wireless users. The Aruba wireless solution is an ArubaOS 8.x Mobility Master (MM) deployment. ClearPass sends an Aruba VSA role name for an authenticated user. However, the administrator notices that the role assigned to the user is different from the one assigned by the ClearPass server.

Which two items should the administrator verify that might be the cause of this problem? (Choose two.)

- A. Enablement of user roles on the controller
- B. Spelling of the role on the ClearPass server
- C. Server-derived role assignment on the ClearPass server
- D. Role existence on the Managed Network
- E. Order assignment that the controller uses to select a user role

Correct Answer: BD

QUESTION 2

Refer to the exhibit.

Last synchronization time: Thu Apr 13 07:42:48 2017

To Master Switch at 10.254.10.101: succeeded

WMS Database backup file size: 39121 bytes

Local User Database backup file size: 29694 bytes

Global AP Database backup file size: 13375 bytes

IAP Database backup file size: 3750 bytes

Airgroup Database backup file size: 3052 bytes

License Database backup file size: 5358 bytes

CPSec Database backup file size: 3224 bytes

Bocmgr Database backup file size: 6016 bytes

Synchronization took 1 second

1 synchronization attempted

0 synchronization have failed

Periodic synchronization is enabled and runs every 60 minutes

Synchronization doesn't include Captive Portal Custom data

Airmatch database gets synchronized periodically. Last synchronization time:

2017-04-13 07:22:2019:20:24

What can be determined from the command output shown in the exhibit?

- A. The synchronized data is protected by VRRP.
- B. The command was executed on the standby Mobility Master (MM).
- C. The synchronization period is at its default value.
- D. The other Mobility Master (MM) is the active license server.

Correct Answer: C

QUESTION 3

Refer to the exhibit.

```
Local          Master          Server (LMS)    State
LMS Type      IP Address      State           Capability Role
Primary       : 10.1.20.100  Complete       Per User Operational Primary

Switch Anchor Controller (SAC) State

          IP Address      Mac Address      State
          SAC       :10.1.20.100  000b86-b6d007   Registered
Standby-SAC  :10.1.20.101  00b86-b6b177   Registered

User Anchor Controller (UAC) : 10.1.20.100

User          Port          VLAN          State          Bucket ID
643150-a153e3  22           21            Registered     49

User Anchor Controller (UAC) : 10.1.20.101

User          Port          VLAN          State          Bucket ID
005056-9fead9  20           21            Registered     172
```

What can an administrator determine from this Aruba device output?

- A. A switch is connected to a standalone Mobility Controller.
- B. An AP is connected to a Mobility Controller in a cluster.
- C. An AP is connected to a standalone Mobility Controller.
- D. A switch is connected to a Mobility Controller in a cluster.

Correct Answer: D

QUESTION 4

An administrator supports an Aruba wireless network. The administrator configures an AAA profile referenced in a WLAN profile, where:

The initial role assigned in the AAA profile is logon The MAC authentication default role is guest The 802.1X authentication role is authenticated

ClearPass is used to verify the 802.1X user credentials. A user authenticates and is assigned the authenticated default role instead of the role assigned in the ClearPass server configuration.

What must the administrator do so that the ClearPass role is assigned to the user?

- A. Select the Server-derived roles User Role in the AAA profile.

- B. Verify the role exists on the controller.
- C. Create the Download Role from CPPM User Rule.
- D. Select the Server-derived roles in the Server Group section.

Correct Answer: D

QUESTION 5

An administrator defines credentials in the Mobility Master> Configuration> System section to configure a Mobility Master (MM). The administrator then accesses AirWave and adds the MM in Monitor-Only mode. The administrator expects AirWave to automatically discover the Aruba Virtual Mobility Controllers (VMCs) also managed by the MM, but does not see these under APs/Devices> New section in AirWave.

What should the administrator do to solve this problem?

- A. Enable Automatic Device Authorization for the Group the Mobility Master belongs to in AirWave.
- B. Define AirWave communication parameters for the Virtual Mobility Controllers on the Mobility Master, and then scan for the Virtual Mobility Controllers in AirWave.
- C. Define the AirWave communication parameters on the Virtual Mobility Controllers, and then scan for the Virtual Mobility Controllers in AirWave.
- D. Define AirWave communication parameters for the Virtual Mobility Controllers on the Mobility Master, and have AirWave repoll the Mobility Master.

Correct Answer: D

[HPE6-A71 VCE Dumps](#)

[HPE6-A71 Exam Questions](#)

[HPE6-A71 Braindumps](#)