

# JN0-102<sup>Q&As</sup>

Juniper Networks Certified Internet Associate, Junos(JNCIA-Junos)

## Pass Juniper JN0-102 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/jn0-102.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

-- Exhibit -[edit policy-options policy-statement my-policy]

```
user@router# show
```

```
term 1 {
```

```
from {
```

```
route-filter 192.168.0.0/16 orlonger;
```

```
}
```

```
then accept;
```

```
}
```

-- Exhibit -Referring to the exhibit, which three networks match the policy? (Choose three.)

- A. 192.168.0.0/16
- B. 192.168.0.0/15
- C. 192.168.65.0/24
- D. 192.167.0.0/17
- E. 192.168.24.89/32

Correct Answer: ACE

---

## QUESTION 2

You are asked to change the cable on interface ge-2/1/3. Which statement is correct?

- A. The cable is found on FPC 1, slot 3, and port 2.
- B. The cable is found on slot 1, port 2, and FPC 3.
- C. The cable is found on port 3, FPC 2, and slot 1.
- D. The cable is found on FPC 1, slot 2, and port 3.

Correct Answer: C

---

## QUESTION 3

What is the central processing component of the forwarding plane?

- A. PFE

- B. RE
- C. Junos OS
- D. forwarding table

Correct Answer: A

---

#### QUESTION 4

What represents the decimal equivalence of 11100111?

- A. 195
- B. 223
- C. 230
- D. 231

Correct Answer: D

---

#### QUESTION 5

Which two statements are true about the primary address on an interface? (Choose two.)

- A. It is the address used by default as the local address for broadcast and multicast packets sourced locally and sent out of the interface.
- B. You use the primary address when you have multiple IP addresses belonging to the same subnet on the same interface.
- C. It can be useful for selecting the local address used for packets sent out of unnumbered interfaces when multiple non-127 addresses are configured on the loopback interface.
- D. By default, the primary address on an interface is selected as the numerically highest local address configured on the interface.

Correct Answer: AC

[JN0-102 VCE Dumps](#)

[JN0-102 Practice Test](#)

[JN0-102 Exam Questions](#)