

JN0-1361^{Q&As}

Service Provider Design Specialist (JNCDS-SP)

Pass Juniper JN0-1361 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/jn0-1361.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Your customer wants an MPLS-based L3VPN service between multiple remote locations. Which two statements are true regarding the customer's WAN edge devices? (Choose two)

- A. They must have EBGP configured.
- B. They require routes for all remote sites.
- C. They must have MPLS configured.
- D. They require IP connectivity with the PEs.

Correct Answer: BD

QUESTION 2

Your organization maintains container-based applications hosted by two different cloud service providers.

You are asked to design a Layer 2 connection between the two cloud data centers. The data center interconnect solution must support control plane MAC learning.

Which Layer 2 data center interconnect model satisfies this requirement?

- A. L3VPN
- B. L2VPN
- C. VPLS
- D. EVPN

Correct Answer: D

QUESTION 3

Which statement is correct regarding classifiers in CoS?

- A. Classifiers are used to route traffic between routing instances.
- B. Classifiers are used to define the transmit rate for forwarding classes.
- C. Classifiers are used to separate traffic into different forwarding classes.
- D. Classifiers are used to change DiffServ values on outgoing packets.

Correct Answer: C

QUESTION 4

Your customer requires redundant routers and wants to use VRRP for the default gateway at their Internet edge. Which two statements are correct in this scenario? (Choose two)

- A. VRRP will only support two routers
- B. The VRRP master and backup send advertisements to each other at regular intervals.
- C. VRRP dynamically elects master and backup routers
- D. VRRP for IPv6 provides a much faster switchover to an alternate default router than IPv6 neighbor discovery procedures

Correct Answer: BC

QUESTION 5

You are asked to design a BNG solution using MX Series routers. You want to dynamically assign per-subscriber configuration parameters using VSAs.

Which external service is required to accomplish this task?

- A. DHCP
- B. 802.1X
- C. RADIUS
- D. TACACS

Correct Answer: C

[Latest JN0-1361 Dumps](#)

[JN0-1361 VCE Dumps](#)

[JN0-1361 Practice Test](#)