

## JN0-332<sup>Q&As</sup>

Juniper Networks Certified Internet Specialist, SEC (JNCIS-SEC)

### Pass Juniper JN0-332 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.lead4pass.com/jn0-332.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



## QUESTION 1

You are attempting to set up an IPsec VPN between an SRX240 and another vendor's firewall. The phase 1 security associations are up, but the phase 2 security associations are not present. What is the problem?

- A. Proxy ID mismatch
- B. IKE mode mismatch
- C. Preshared key mismatch
- D. IKE peer mismatch

Correct Answer: A

---

## QUESTION 2

-- Exhibit -

[edit security policies]

user@host# show

```
from-zone hr to-zone internet {
```

```
  policy internet-access {
```

```
    match {
```

```
      source-address any;
```

```
      destination-address any;
```

```
      application any;
```

```
    }
```

```
  then {
```

```
    permit;
```

```
  }
```

```
}
```

```
policy clean-up {
```

```
  match {
```

```
    source-address any;
```

```
    destination-address any;
```

```
application any;
```

```
}
```

```
then {
```

```
deny;
```

```
}
```

```
}
```

```
}
```

-- Exhibit -

Click the Exhibit button.

You want to permit access to the Internet from the hr zone during a specified time.

Which configuration will accomplish this task?

- A. Configure a scheduler, apply it to a new policy, and insert it after internet-access to permit Internet access.
- B. Configure a scheduler and apply it to the policy internet-access to deny Internet access.
- C. Configure a scheduler and apply it to the policy internet-access to permit Internet access.
- D. Configure a scheduler, apply it to a new policy, and insert it before internet-access to permit Internet access.

Correct Answer: C

---

### QUESTION 3

You must configure a SCREEN option that would protect your router from a session table flood. Which configuration meets this requirement?

- A. `[edit security screen] user@host# show ids-option protectFromFlood { icmp { ip-sweep threshold 5000; flood threshold 2000; } }`
- B. `[edit security screen] user@host# show ids-option protectFromFlood { tcp { syn-flood { attack-threshold 2000; destination-threshold 2000; } } }`
- C. `[edit security screen] user@host# show ids-option protectFromFlood { udp { flood threshold 5000; } }`
- D. `[edit security screen] user@host# show ids-option protectFromFlood { limit-session { source-ip-based 1200; destination-ip-based 1200; } }`

Correct Answer: D

---

### QUESTION 4

Which statement describes a security zone?

- A. A security zone can contain one or more interfaces.
- B. A security zone can contain interfaces in multiple routing instances.
- C. A security zone must contain two or more interfaces.
- D. A security zone must contain bridge groups.

Correct Answer: A

---

## QUESTION 5

You want to show interface-specific zone information and statistics. Which operational command would be used to accomplish this?

- A. show security zones detail
- B. show interfaces ge-0/0/3.0
- C. show interfaces terse
- D. show interfaces ge-0/0/3.0 extensive

Correct Answer: D

[JN0-332 PDF Dumps](#)

[JN0-332 VCE Dumps](#)

[JN0-332 Study Guide](#)