

JN0-348^{Q&As}

Enterprise Routing and Switching, Specialist

Pass Juniper JN0-348 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/jn0-348.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Click the Exhibit button.

```
{master:0}
user@switch> show spanning-tree interface

Spanning tree interface parameters for instance 0

Interface      Port ID      Designated      Designated      Port      State  Role
                port ID      port ID         bridge ID      Cost
ge-0/0/8.0     128:521     128:521         8192.50c58daedb41  200  FWD   DESG
ge-0/0/9.0     64:522      64:522          8192.50c58daedb41  2000 FWD   DESG
ge-0/0/14.0    240:527     240:527         8192.50c58daedb41  20000 FWD   DESG
ge-0/0/15.0    128:528     128:528         8192.50c58daedb41  200000 FWD   DESG
```

Based on the output shown in the exhibit, which statement is correct?

- A. The ge-0/0/9 interface is using the default priority value.
- B. This switch has a bridge priority of 8k.
- C. This switch is currently blocking all traffic.
- D. The ge-0/0/15 interface is using the default port cost.

Correct Answer: B

QUESTION 2

You are enabling dynamic ARP inspection on an EX4300 switch.

Which service is enabled by default in this scenario?

- A. DHCP snooping
- B. persistent MAC learning
- C. MAC limiting
- D. IP Source Guard

Correct Answer: A

QUESTION 3

When electing a DIS in an IS-IS network, what is used to break a priority tie?

- A. highest MAC address
- B. highest router ID
- C. lowest MAC address
- D. lowest router ID

Correct Answer: A

QUESTION 4

You have configured the router with an IS-IS interface metric of 2048. However, the IS-IS interface metric of 63 is being applied for the interface of this router.

What must you do to enable the larger metric value?

- A. Enable wide metrics.
- B. Disable narrow metrics.
- C. Restart the IS-IS protocol.
- D. Enable level 1 IS-IS routing.

Correct Answer: A

QUESTION 5

Click the Exhibit button.

```
[edit routing-options]
user@host# show
static {
    defaults {
        preference 180;
    }
    route 0.0.0.0/0 {
        next-hop 172.30.25.1;
        qualified-next-hop 172.30.25.5 {
            preference 7;
        }
    }
}
```

Which statement is true about the configuration shown in the exhibit?

- A. The preference for the 172.30.25.1 next hop is 5.
- B. The preferred next hop is 172.30.25.5.
- C. The preference for the 172.30.25.1 next hop is 7.
- D. 172.30.25.1 is the preferred next hop.

Correct Answer: B

[JN0-348 VCE Dumps](#)

[JN0-348 Study Guide](#)

[JN0-348 Braindumps](#)