VCE & PDF
Lead4Pass.com

JN0-360^{Q&As}

Service Provider Routing and Switching, Specialist (JNCIS-SP)

Pass Juniper JN0-360 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.lead4pass.com/JN0-360.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

What are two benefits of using MVRP? (Choose two.)

A. It reduces network administration and overhead

B. It dynamically creates and prunes VLANs

C. It provides redundancy for Layer 2 interfaces

D. It dynamically translates Layer 2 addresses to Layer 3 addresses

Correct Answer: AB

The Multiple VLAN Registration Protocol (MVRP) simplifies VLAN management by dynamically managing VLAN registration in a LAN. MVRP helps reduce administration and network overhead by dynamically pruning VLAN information when a switch no longer has active access ports, and by dynamically creating newly configured VLANs.

QUESTION 2

What are two methods for decreasing the size of an OSPF link-state database (LSDB)? (Choose two.)

A. Ensure that all routers on a shared segment are configured with a priority value of 0.

B. Use an interface type of p2p when possible.

C. Segment large groups of routers into areas.

D. Change a stub area to NSSA when possible.

Correct Answer: BC

QUESTION 3

In an IS-IS network, which device represents the pseudonode?

A. a designated intermediate system

B. an area border router

C. a router with an IS-IS export policy

D. a router connected to the backbone

Correct Answer: A

On broadcast networks in the IS-IS protocol, the elected DIS creates the pseudo-node, which represents itself and advertises it into the network at the appropriate level.

QUESTION 4

-- Exhibit -protocols {

isis {

level 1 disable;

interface ge-1/0/0.0 {

level 2 disable;

}

interface ge-1/1/0.0;

interface lo0.0;

}

}

-- Exhibit -

Click the Exhibit button.

Referring to the exhibit, what is the resulting behavior on interface ge-1/0/0?

A. Level 1 is enabled.

B. Level 1 is disabled.

C. Level 2 is enabled.

D. Level 1 and Level 2 are disabled.

Correct Answer: A

QUESTION 5

What are three BGP attributes used in the route-selection process? (Choose three.)

A. local preference

B. communities

C. MED

D. origin

E. atomic aggregate

Correct Answer: ACD

When a Junos device receives two similar route advertisements from different BGP peers, it will select the route will the

lowest MED value. BGP route selection proceeds in this manner:

Prefer the highest local-preference value

Prefer the shortest AS-path length

Prefer the lowest origin value

Prefer the lowest MED value

Prefer routes learned from an EBGP peer over an IBGP peer

Prefer best exit from AS

For EBGP-receive routes, prefer the current active route:

otherwise, prefer routes from the peer with the lowest RID

Prefer paths with the shortest cluster length

Prefer routes from the peer with the lowest peer ID

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: