

JN0-362^{Q&As}

Service Provider Routing and Switching - Specialist (JNCIS-SP)

Pass Juniper JN0-362 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/jn0-362.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Click the Exhibit button.

```
[edit protocols]
user@router# show ospf
area 0.0.0.0
    interface ge-0/0/1.0
        bfd-liveness-detection {
            minimum-interval 300;
        multiplier 4;
            session-mode automatic;
        }
    }
}
```

Referring to the exhibit, how many milliseconds must pass before the interface ge-0/0/1.0 is considered down?

- A. 1200 ms
- B. 900 ms
- C. 1600 ms
- D. 2400 ms

Correct Answer: A

QUESTION 2

You must establish an MPLS LSP between two locations. You are required to ensure that the LSP traverses specific routers within the network.

Which solution is correct in this scenario?

- A. Enable traffic engineering within RSVP and enable the Fast Reroute feature
- B. Implement RSVP and define the explicit route the LSP must follow
- C. Implement LDP and define the explicit route the LSP must follow
- D. Enable traffic engineering within LDP and define the explicit route the LSP must follow

Correct Answer: B

QUESTION 3

Click the Exhibit button.

```
[edit policy-options]
user@R1# show
policy-statement direct2ospf {
    term 1 {
        from {
            protocol direct;
            route-filter 172.10.1.0/24 exact;
        }
        then accept;
    }
}

[edit protocols]
user@R1# show
ospf {
    export direct2ospf;
    area 0.0.0.1 {
        interface ge-1/0/0.0;
    }
}

[edit protocols]
user@R2# show
ospf {
    area 0.0.0.0 {
        interface ge-0/0/0.0;
        interface ge-0/0/1.0;
        interface lo0.0;
    }
    area 0.0.0.1 {
        interface ge-1/0/0.0;
    }
}
```

Referring to the exhibit, which statement is correct?

- A. R2 is an ASBR
- B. R1 is a backbone router
- C. R2 is an ABR
- D. R1 is an ABR

Correct Answer: C

QUESTION 4

Which IPv6 extension header notifies intermediary devices that they must inspect the packet's options?

- A. destination options header
- B. routing header
- C. hop-by-hop options header
- D. fragment header

Correct Answer: B

Reference: https://en.wikipedia.org/wiki/IPv6_packet

QUESTION 5

Which two statements are correct about the BGP MED attribute? (Choose two.)

- A. BGP uses the MED value when peering to two or more connections to the same upstream AS
- B. BGP routes require the MED attribute be defined
- C. BGP uses the MED value when peering to two different upstream ASs
- D. BGP assumes the MED value to be 0, if not already defined

Correct Answer: AD

Reference: https://www.juniper.net/documentation/en_US/junos/topics/topic-map/med-attribute.html

[Latest JN0-362 Dumps](#)

[JN0-362 VCE Dumps](#)

[JN0-362 Exam Questions](#)