

JN0-420^{Q&As}

Automation and DevOps, Specialist (JNCIS-DevOps)

Pass Juniper JN0-420 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/jn0-420.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Click the Exhibit button. Exhibit:

```
- - -
-   name: Get facts from Junos devices
    hosts: all
    connection: local
    gather_facts: no
    roles:

-   Juniper.junos

tasks:

-   name: Get facts from Junos devices

        junos_get_facts:
            host: "{{inventory_hostname}}"
            user: "user"
            passwd: "user123"
            register: response

-   name: Print Junos version
    debug:
        var: response.facts.version
```

The Ansible playbook shown in the exhibit is executed against a set of Junos network devices. Each Junos device is configured with a user account in the super-user login class. The user account uses SSH-keybased authentication with a passphrase of user123.

What is the result of executing this playbook against the Junos network devices?

- A. The playbook executes, but fails with a "ConnectAuthError" due to the missing passphrase argument to the junos_get_facts module
- B. The playbook fails due to a YAML syntax error.
- C. The playbook executes and prints the version of Junos running on each network device as the value of response.facts.version
- D. The playbook executes and prints "VARIABLE IS NOT DEFINED!" as the value response.facts.version

Correct Answer: C

QUESTION 2

Click the Exhibit button. Exhibit:

```
user@router> show configuration system services
ssh {
    root-login allow;
    protocol-version v2;
}
netconf {
    rfc-compliant;
}
```

You are validating access to a Junos device using NETCONF and receive the response shown below.

```
user@host$ ssh 192.0.2.2 -l user -p830
ssh: connect to host 192.0.2.2 port 830: Connection refused
user@host$
```

Referring to the exhibit, how would you solve this issue?

- A. Enable traceoptions under the NETCONF configuration hierarchy
- B. Enable protocol-version v1 under the SSH configuration hierarchy
- C. Enable outbound-ssh with services netconf under the SSH configuration hierarchy
- D. Enable ssh under the NETCONF configuration hierarchy

Correct Answer: C

Reference: https://www.juniper.net/documentation/en_US/junos/topics/topic-map/netconf-sshconnection.html

QUESTION 3

Which statement describes the relationship between YANG and NETCONF?

- A. YANG is the programming language used to generate base classes to develop the NETCONF protocol
- B. NETCONF models XML data used to program YANG modules
- C. YANG models the state and configuration data manipulated by the NETCONF protocol
- D. NETCONF is the programming language used to create the state and configuration data manipulated by YANG

Correct Answer: C

Reference: <https://tools.ietf.org/html/rfc6020>

QUESTION 4

You want to enable an unsigned Python op script named inventory.py that will be stored on a local Junos device.

Which two commands are needed to accomplish this task? (Choose two)

- A. set system scripts op allow-url-for-python
- B. set system scripts op file inventory.py
- C. set system scripts op no-allow-url
- D. set system scripts language python

Correct Answer: BD

Reference: https://www.juniper.net/documentation/en_US/junos/topics/example/junos-script-automationop-script-changing-configuration-python.html

QUESTION 5

Which data serialization method does the Junos CLI use to communicate with the Junos management process (mgd)?

- A. JSON
- B. gRPC
- C. XML
- D. YAML

Correct Answer: C

[JN0-420 VCE Dumps](#)

[JN0-420 Study Guide](#)

[JN0-420 Exam Questions](#)