

JN0-533^{Q&As}

FWV, Specialist (JNCIS-FWV)

Pass Juniper JN0-533 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/jn0-533.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

How is a route-based VPN different from a policy-based VPN?

- A. A route-based VPN requires manual keys for encryption and authentication.
- B. A route-based VPN requires static route entries for the remote peer.
- C. A route-based VPN is bound to a tunnel interface.
- D. A route-based VPN is bound to a loopback interface.

Correct Answer: C

QUESTION 2

Referring to the exhibit, which three statements are true? (Choose three.)

```
NS5200(M)-> get nsrp nsrp version: 2.0 cluster info: cluster iD. 1, namE. 5200 local unit iD. 8000208 active units
discoveredD. index: 0, unit iD. 8014208, ctrl maC. 0010db000085, data maC. 0010db000086 index: 1, unit iD. 8337344,
ctrl maC. 0010db0000c5, data maC. 0010db0000c6 total number of units: 2 VSD group info: init hold timE. 5 heartbeat
lost thresholdD. 3 heartbeat interval: 200(ms) master always exist: enabled group priority preempt holddown inelig master
PB other members 0 50 yes 45 no myself 8330044 total number of vsd groups: 1 Total iteration=
,time=878546093,max=4900,min=170,average=18 RTO mirror info: run time object synC. enabled ping session synC.
enabled coldstart sync done nsrp data packet forwarding is enabled nsrp link info: control channel: ha1 (ifnum: 5) maC.
0010db000085 statE. up data channel: ha2 (ifnum: 6) maC. 0010db000086 statE. up ha secondary path link not
available NSRP encryption: disabled NSRP authentication: disabled device based nsrp monitoring thresholD. 255,
weighted sum: 0, not failed device based nsrp monitor interfacE. ethernet2/1(weight 255, UP) ethernet2/3(weight 255,
UP) ethernet2/4(weight 255, UP) ethernet2/5(weight 255, UP) ethernet2/2 (weight 255, UP) device based nsrp monitor
zonE. device based nsrp track ip: (weight: 255, disabled) number of gratuitous arps: 4 (default) config synC. enabled
track ip: disabled
```

- A. This cluster is configured as an active/active cluster.
- B. RTO sync is enabled.
- C. No secondary path is configured.
- D. master-always-exists is enabled.
- E. Only one interface is used for both the control and data links.

Correct Answer: BCD

QUESTION 3

When using NSRP, which command will insure uninterrupted communications for VPNs using certificates for authentication?

- A. set hostname

- B. set NSRP clustername
- C. set NSRP cluster name
- D. set NSRP cluster hostname

Correct Answer: C

QUESTION 4

A ScreenOS device evaluates five primary elements when performing a security policy check on a new session. Which five elements are evaluated?

- A. source IP address, destination IP address, source route, source port, and destination port
- B. source IP address, destination IP address, source port, destination port, and protocol
- C. source IP address, destination IP address, source port, destination port, and payload
- D. destination IP address, source port, destination port, protocol, and payload

Correct Answer: B

QUESTION 5

What is the function of NAT?

- A. It performs Layer 3 routing.
- B. It evaluates and redirects matching traffic into secure tunnels.
- C. It provides translation between IP addresses.
- D. It performs Layer 2 switching.

Correct Answer: C

[JN0-533 Practice Test](#)

[JN0-533 Study Guide](#)

[JN0-533 Braindumps](#)