

JN0-660^{Q&As}

Service Provider Routing and Switching, Professional

Pass Juniper JN0-660 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/jn0-660.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibit.

```
[edit routing-options]
user@router# show
autonomous-system 1;
```

```
[edit protocols]
user@router# show
bgp {
  group peer-AS2 {
    type external;
    export policy-1;
    peer-as 2;
    neighbor 10.10.10.2;
  }
}
```

```
[edit policy-options]
user@router# show
policy-statement policy-1 {
  then as-path-prepend "1 1 1 1";
}
```

What is the expected result based on the configuration shown in the exhibit?

- A. To discourage IBGP routers from using the path through 10.10.10.2
- B. To encourage IBGP routers to use the path through 10.10.10.2
- C. To discourage EBGP routers from using the path through 10.10.10.2
- D. To encourage EBGP routers to use the path through 10.10.10.2

Correct Answer: C

QUESTION 2

Which two statements correctly describe BGP operation? (Choose two.)

- A. IBGP does not advertise routes learned from other IBGP neighbors.
- B. IBGP advertises routes learned from other IBGP neighbors.
- C. EBGP advertises routes learned from other IBGP or EBGP neighbors.
- D. EBGP does not advertise routes learned from other EBGP neighbors.

Correct Answer: AC

QUESTION 3

You are asked to provide redundancy to avoid a single point of failure for your route reflector cluster groups.

Which action will accomplish this task?

- A. Configure unique cluster IDs for each client within a route reflector cluster group.
- B. Configure two route reflectors for each route reflector cluster group.
- C. Configure a full IBGP peer mesh between clients within the route reflector cluster group.
- D. Configure the no-client-reflect parameter on the route reflector.

Correct Answer: B

QUESTION 4

You are asked to configure auto-RP as part of a new PIM sparse mode deployment in your network. Which two configuration tasks are required? (Choose two.)

- A. All RP routers must be configured with the mapping auto-RP role.
- B. All RP routers must be configured with the discovery auto-RP role.
- C. All non-RP routers must be configured with the mapping auto-RP role.
- D. All non-RP routers must be configured with the discovery auto-RP role.

Correct Answer: AD

QUESTION 5

You are asked to deploy VPLS in your network as a new service for several customers and must identify the configuration and provisioning requirements. Which two statements are correct? (Choose two.)

- A. PE routers must include a VRF routing instance.
- B. PE interfaces facing customers must have family VPLS configured.
- C. PE routers must create a unique site ID for each CE device.
- D. CE routers must be configured with their assigned route target.

Correct Answer: BC

[Latest JN0-660 Dumps](#)

[JN0-660 VCE Dumps](#)

[JN0-660 Exam Questions](#)