

## JN0-681<sup>Q&As</sup>

New Data Center, Professional

### Pass Juniper JN0-681 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/jn0-681.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

What are three advantages of using MPLS for data center interconnects? (Choose three.)

- A. dedicated MPLS backbones for Layer 2 and Layer 3 DCIs
- B. any-to-any connectivity
- C. traffic engineering
- D. dedicated connections between customer sites
- E. sub 50 ms failover times

Correct Answer: ACE

---

**QUESTION 2**

Which EVPN route type prevents BUM traffic from looping back to a multihomed host?

- A. IP prefix route
- B. Ethernet autodiscovery route
- C. Ethernet segment route
- D. inclusive multicast-Ethernet tag route

Correct Answer: B

---

**QUESTION 3**

You are asked to configure VXLAN for your data center using multicast to exchange VTEP information.

In this scenario, which two configuration parameters must match on the VTEPs in the same VXLAN segment? (Choose two.)

- A. multicast group
- B. VLAN ID
- C. routing instance name
- D. VNI

Correct Answer: AD

---

**QUESTION 4**

What are two methods used to scale an IBGP IP Fabric? (Choose two.)

- A. spanning tree
- B. redundant trunk groups
- C. route reflection
- D. confederations

Correct Answer: CD

---

## QUESTION 5

You are configuring an IP Fabric in your data center and you are trying to load-balance traffic across multiple equal-cost BGP routes. You have enabled multipath, but the traffic is not being load-balanced.

```
user@switch> show route 10.1.2.0/24

inet.0: 11 destinations, 13 routes (11 active,
holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both

10.1.2.0/24          *[BGP/170] 01:21:05,
localpref 100
                    AS path: 64516 I,
validation-state:  unverified
                    to 172.16.3.1 via ge-
0/0/1.0
                    > to 172.16.5.1 via ge-
0/0/2.0
                    [BGP/170] 01:09:08,
localpref 100
                    AS path: 64515 I,
validation-state:  unverified
                    > to 172.16.3.1 via ge-
0/0/1.0

user@switch> show route forwarding-table
destination 10.1.2.0/24
Routing table: default.inet
Internet:
Destination          Type RtRef Next hop
                    Type Index  NhRef Netif
10.1.2.0/24          user   0 172.16.5.1
                    ucst   574 4 ge-0/0/2.0
...

user@switch> show configuration policy-options
policy-statement load-balance {
    term lb {
        then {
            load-balance per-packet;
            accept;
        }
    }
}
```

Referring to the exhibit, what will solve this problem?

- A. You should apply the load-balance policy as an import policy to the forwarding table.
- B. You should apply the load-balance policy as an import policy for the BGP neighbor.
- C. You should apply the load-balance policy as an export policy to the forwarding table.
- D. You should apply the load-balance policy as an export policy to the BGP neighbor.

Correct Answer: C

[JN0-681 VCE Dumps](#)

[JN0-681 Study Guide](#)

[JN0-681 Exam Questions](#)