

NCS-CORE^{Q&As}

Nutanix Certified Services Core Infrastructure Professional

Pass Nutanix NCS-CORE Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.lead4pass.com/ncs-core.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nutanix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A customer wants to run SAP HANA on a Nutanix cluster with the following characteristics:

AHV nodes SAP HANA version 2 Production database files

Which configuration should be recommended to the customer?

- A. Start with a cluster containing three or more nodes
- B. Enable only compression for the container that contains the Production database
- C. Do not enable compression, deduplication, or erasure coding on the storage container
- D. Place the SAP HANA Database on the same socket as CVM

Correct Answer: C

QUESTION 2

An administrator needs to deploy an application with a large amount of data connected via Nutanix Volumes. Which two actions should the administrator take when designing the Volume Group? (Choose two.)

- A. Use multiple subnets for iSCSI traffic
- B. Enable RSS (Receive Side Scaling)
- C. Enable thick provisioning on the Volume Group(s)
- D. Distribute workload across multiple virtual disks

Correct Answer: BD

QUESTION 3

A consultant deploys a four-node VMware ESXi cluster and vCenter server. An HA/DRS cluster is configured for all four nodes. The customer deploys five new VMs on the cluster.

During the knowledge Transfer, a network cable on one node is removed to demonstrate HA and migration of the VMs to another host. In the HA/DRS cluster settings, the VM Restart Priority for all CVMs is set to Disabled. The customer

observes warnings that the CVM on the ejected host is no longer powered on.

Which ESXi HA/DRS cluster setting is missing?

- A. Enable EVC for the cluster.
- B. Disable VM Monitoring on all CVMs.

- C. Disable Automation Level on all CVMs.
- D. Enable Host Monitoring.

Correct Answer: C

QUESTION 4

A customer has a G6 AHV cluster with 4x10GbE NICs on each node and the following configuration:

*

Networking is set to default

*

Only two NICs are connected

The customer receives the following critical message:

The NIC is disconnected from the switch, or the switchport is failing.

What should the consultant verify to resolve the issue?

- A. The NICs are configured for active-backup.
- B. The VLANs are configured correctly on the switch or tagged on the cluster.
- C. The other two 10GbE connections are removed from the default bond.
- D. The NICs are connected for balance-slb.

Correct Answer: A

QUESTION 5

A customer has a primary datacenter with 12 Nutanix blocks distributed across three racks. The customer wants to achieve the most resiliency possible. They also have a datacenter in a branch office that is 400 kilometers away from the primary datacenter.

Which two solutions should be used? (Choose two.)

- A. Time Stream to a remote site
- B. Async DR to a remote site
- C. Rack awareness
- D. Block awareness

Correct Answer: BC

[NCS-CORE PDF Dumps](#)

[NCS-CORE VCE Dumps](#)

[NCS-CORE Exam
Questions](#)