

NS0-162^{Q&As}

NetApp Certified Data Administrator (ONTAP)

Pass NetApp NS0-162 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-162.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

You have a remote FlexCache storage device that is running on ONTAP Select 9.8 software. The cache origin volume is on an FAS8700 that is running ONTAP 9.8 software. The WAN connection dropped, and the FlexCache volume is in disconnected mode.

In this scenario, which LIFs would you ping to troubleshoot the disconnect?

- A. management
- B. Intercluster
- C. data
- D. cluster

Correct Answer: D

Explanation: https://docs.netapp.com/ontap-9/topic/com.netapp.doc.pow-fc-mgmt/GUID-AE9CC59E-BE3B-4185-B018-E3F089CB53B0.html?cp=17_0_2

QUESTION 2

After deploying an AFF A400, you want to deploy a storage virtual machine (SVM) to serve SMB data. Which three conditions must exist in this scenario? (Choose three.)

- A. You must have sufficient space for the root volume.
- B. You must have a non-root aggregate in the online state.
- C. You must have encryption enabled on the root volume.
- D. You must synchronize the cluster time.
- E. You must have configured the export policies.

Correct Answer: ADE

QUESTION 3

After deploying an ONTAP 9.8 cluster, you want to disable the unused Ethernet ports. In this scenario, which two methods would accomplish this task? (Choose two.)

- A. Use ONTAP System Manager.
- B. Use the command line interface.
- C. Use Active IQ Config Advisor.
- D. Use Active IQ Unified Manager.

Correct Answer: AB

QUESTION 4

Exhibit

The exhibit shows three panels from the ONTAP System Manager interface:

- IPspaces:** A list with two entries:
 - Cluster: Broadcast Domains Cluster
 - Default: Storage VMS svm1_cluster1, svm2_cluster1
- Broadcast Domains:** A table showing broadcast domains:

	cluster1-01	e0a	e0b
	cluster1-02	e0a	e0b
Default	1500 MTU	IPspace: Default	
	cluster1-01	e0c	e0d e0e e0f e0g
	cluster1-02	e0c	e0d e0e e0f e0g
- Network Interfaces:** A table listing network interfaces:

Name	Status	Storage VM	IPspace	Address	Current Node	Current P...	Protocols
if_svm1_cluster1_881	✓	svm1_cluster1	Default	192.168.0.132	cluster1-01	e0d	
cluster_mgmt	✓		Default	192.168.0.101	cluster1-01	e0c	
if_svm2_cluster1_4	✓	svm2_cluster1	Default	192.168.0.135	cluster1-01	e0e	ISCSI
if_svm2_cluster1_978	✓	svm2_cluster1	Default	192.168.0.130	cluster1-01	e0c	ISCSI

You have Installed a new ONTAP 9.8 cluster and want to move the e0e and e0c ports into a new broadcast domain. Referring to the exhibit, which action satisfies this requirement?

- A. Use the `broadcast-domain create` command
- B. Use the `broadcast-domain split` command.
- C. Use ONTAP System Manager to create a new broadcast domain.
- D. Use the `broadcast-domain= merge` command.

Correct Answer: B

QUESTION 5

You want to monitor system performance in real time.

In this scenario, which two tools would you use to accomplish this task? (Choose two.)

- A. ONTAP System Manager

B. Active IQ Unified Manager

C. ONTAP CLI

D. Active IQ Digital Advisor

Correct Answer: AC

[NS0-162 PDF Dumps](#)

[NS0-162 VCE Dumps](#)

[NS0-162 Exam Questions](#)