

## NS0-173<sup>Q&As</sup>

Cisco and NetApp FlexPod Design Specialist

### Pass NetApp NS0-173 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-173.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

A customer is investigating options for implementing a FlexPod Datacenter solution that is using vSphere

6.x.

A.

Cisco Cloud Center documentation

B.

Cisco Validated Design documents

C.

VMware vSAN documentation

D.

NetApp Technical Report

Correct Answer: BD

In this scenario, which two resources would be important to review? (Choose two.)

Reference: [https://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/UCS\\_CVDs/flexpod\\_esxi60\\_n9k.html](https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/UCS_CVDs/flexpod_esxi60_n9k.html)

---

## QUESTION 2

The storage administrator must change the vHBA settings bound to a template associated with a production server.

What happens when the settings are reconfigured in this scenario?

A. The vHBA configuration change does not affect LUN access.

B. The server that is associated with the service profile reboots.

C. The service profile template that is associated with the server is initialized.

D. The vHBA template is deleted from UCS Manager.

Correct Answer: C

---

## QUESTION 3

A customer has installed FlexPod and verified that all wiring connections are correct. However, the customer cannot see any FC LUNs from the NetApp AFF systems.

In this scenario, which three configuration elements should the customer verify? (Choose three.)

- A. FC zoning
- B. igroup configuration
- C. ALUA settings
- D. FC portsets E. MTU configuration

Correct Answer: BDE

---

## QUESTION 4

A customer wants to deploy a FlexPod solution that involves directly connecting the NetApp AFF storage using the FCoE protocol to the Cisco UCS Fabric Interconnects.

In this scenario, which Cisco UCS Fibre Channel mode would be used to accomplish this task?

- A. trunk mode
- B. end host mode
- C. switching mode
- D. access mode

Correct Answer: C

Reference: <https://www.netapp.com/media/16411-nva-0025-deploy.pdf>

---

## QUESTION 5

You are a data center architect at a service provider. You need to configure a new multi-tenant FlexPod service offering.

Which three UCS Manager features will you need to accomplish this task? (Choose three.)

- A. auto discovery
- B. role-based access control
- C. service profiles
- D. virtualization support
- E. policies

Correct Answer: BCE