

NS0-182^{Q&As}

NetApp Certified Storage Installation Engineer, ONTAP

Pass NetApp NS0-182 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-182.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Your customer regularly schedules disaster recovery tests to ensure the high availability capabilities of the ONTAP cluster.

In this scenario, which two commands would you use to perform this test? (Choose two.)

- A. system node run -node NetApp-Cluster-02 -command cf takeover
- B. storage failover giveback -of-node NetApp-Cluster-02
- C. system node run -node NetApp-Cluster-02 -command cf giveback
- D. storage failover takeover -of-node NetApp-Cluster-02

Correct Answer: BD

QUESTION 2

Which LIF type is used by default for hardware-assisted storage failover communication?

- A. intercluster
- B. node-mgmt
- C. data
- D. cluster-mgmt

Correct Answer: B

Reference: https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-cmpr-950%2Fstorage__failover__hwassist__show.html

QUESTION 3

You need to verify the configuration currently loaded on a Cisco Nexus 3132Q-V cluster switch after applying the RCF.

Which command will accomplish this task?

- A. Use the show bootvar command.
- B. Use the verify config command.
- C. Use the show startup-conf command.
- D. Use the show running-config command

Correct Answer: D

QUESTION 4

You have just replaced a FAS controller with a new controller and installed the appropriate licenses for the new FAS controller.

What are two ways to remove unused licenses in this situation? (Choose two.)

- A. Use OnCommand Unified Manager.
- B. Use OnCommand System Manager.
- C. Use the cluster license clean-up nused command.
- D. Use the system license clean-up nused command.

Correct Answer: BD

QUESTION 5

You were dispatched to add a DS224C to an existing HA pair that has a stack of DS4243 shelves with 1 TB drives and a stack of DS4246 shelves with 1 TB drives. The customer wants to make sure that ACP is cabled for all shelves.

Which two considerations should you advise the customer in this situation? (Choose two.)

- A. ACP communication uses SAS cables and does not require Ethernet cables for IOM12 and IOM6 modules.
- B. ACP communication cannot be used for the DS224C and the DS4243 shelves at the same time.
- C. Out-of-band ACP communication is use by default in ONTAP 9.0 and later software.
- D. The ACP communication has been discontinued beginning with ONTAP 9.5, IOM6, and IOM12 modules.

Correct Answer: AC

[Latest NS0-182 Dumps](#)

[NS0-182 Study Guide](#)

[NS0-182 Braindumps](#)