

NS0-184^{Q&As}

NetApp Certified Storage Installation Engineer, ONTAP

Pass NetApp NS0-184 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-184.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

You are installing a new ONTAP 9.7 cluster and attaching the cluster to two separate networks. Your customer has indicated that the same range of client IP addresses are used on both networks and that the networks are never allowed to communicate with each other.

In this scenario, which ONTAP feature must be configured to securely allow all clients to access ONTAP NAS protocols?

- A. BGP
- B. broadcast domains
- C. routing
- D. IPspaces

Correct Answer: B

Reference: <https://www.netapp.com/media/16885-tr-4182.pdf> (9)

QUESTION 2

While installing a new AFF A400 HA pair, you are unable to add an NTP server from another subnet. You are able to ping the NTP server from the new cluster.

In this scenario, what are two causes of this problem? (Choose two.)

- A. The admin SVM has the wrong gateway.
- B. A firewall is blocking port 123.
- C. The time skew is too great.
- D. The cluster management LIF needs to be in a different IPspace.

Correct Answer: AD

QUESTION 3

What are two ways to identify an AFF All SAN Array system? (Choose two.)

- A. View the ONTAP System Manager system nodes.
- B. View the ONTAP System Manager cluster settings.
- C. Use the cluster image show CLI command.
- D. Use the san config show CLI command.

Correct Answer: AD

Ways to identify an ASA system You can identify an ASA system using ONTAP System Manager or using the ONTAP command line interface (CLI). From the ONTAP System Manager dashboard, you can click on the system nodes. The personality type is displayed as "ASA" for ASA systems. From the CLI, you can use san config show command. The ASA value returns as true for ASA systems

QUESTION 4

After a system panic, the NetApp Support team advises you to run the sldiag command.

Which two actions must be performed before you use this command? (Choose two.)

- A. At the LOADER prompt, type boot_maintenance.
- B. At the storage system prompt, type halt.
- C. At the LOADER prompt, type boot_diags.
- D. At the storage system prompt, type boot_maintenance.

Correct Answer: BC

Reference: <https://docs.netapp.com/platstor/index.jsp?topic=%2Fcom.netapp.doc.hw-plat-diag%2FGUIDB944DDDB-FA1D-4306-8157-2DF02613CA39.html>

QUESTION 5

One of the nodes in your ONTAP 9.7 cluster has failed and is not coming back online.

Which two methods would you use to connect to the node failing to come back online? (Choose two.)

- A. Use the Intelligent Platform Management Interface.
- B. Use the Service Processor Interface.
- C. Use Secure Shell.
- D. Use Telnet.

Correct Answer: BC

[NS0-184 VCE Dumps](#)

[NS0-184 Study Guide](#)

[NS0-184 Braindumps](#)