



NS0-191^{Q&As}

NetApp Certified Support Engineer

Pass Network Appliance NS0-191 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.lead4pass.com/ns0-191.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Network Appliance Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers






QUESTION 1

Click the Exhibit tab.

```
cluster::> cifs share show -vserver SVM1 -share-name test9

Vserver: SVM1
Share: test9
CIFS Server NetBIOS Name: SVM1
Path: /test9
Share Properties: oplocks
browsable
changenotify
Symlink Properties: symlinks
File Mode Creation Mask: -
Directory Mode Creation Mask: -
Share Comment: -
Share ACL: Everyone / No access
domainA\companyusers / Full Control
domainA\interngroup / No access
domainA\temps / Read
File Attribute Cache Lifetime: -
Volume Name: vol9
Offline Files: manual
Vscan File-Operations Profile: standard
Maximum Tree Connections on Share: 4294967295
UNIX Group for File Create: -
```



A storage administrator tells you that a company security mandate was applied to remove all CIFS share level permissions of everyone - full control. Now users are unable to access CIFS shares.

The storage virtual machine (SVM) is named "SVM1" on clustered Data ONTAP 8.3.1. The storage administrator wants to know what can be done to restore full control access to users that are receiving "access denied" errors. The storage administrator has provided you with the vserver cifs share show command output of one of the CIFS shares with issues as shown in the exhibit.

Which two steps must you perform to solve the problem? (Choose two.)

- A. Execute the `::>vserver cifs share access-control delete -vserver SVM1 -share test9 -user-or-group Everyone` command from the controller.
- B. Execute the `::>vserver cifs share access-control delete -vserver SVM1 -share test9 -user-or-group domain\interngroup` command from the controller.
- C. Ensure that, in Active Directory, the desired users are members of the `domainA\temps` group.
- D. Ensure that, in Active Directory, the desired users are members of the `domainA\companyusers` group.

Correct Answer: BD

QUESTION 2



You are preparing to implement a storage virtual machine (SVM) in a SAN configuration. You need to eliminate single points of failure and enable the system to survive component failures. According to NetApp, what is the recommended minimum number of paths per LUN connecting to each node being used by an SVM in a cluster?

- A. 4
- B. 2
- C. 1
- D. 3

Correct Answer: B

QUESTION 3

You receive the AutoSupport message, "CONTROLLER TAKEOVER COMPLETE PANIC" from a FAS3250 controller. You suspect a hardware issue. A core file was written to disk. In this scenario, which two actions would you perform to obtain more information? (Choose two.)

- A. You turn on "hardware debugging mode" using System Manager.
- B. You collect the core file and upload it to NetApp Global Services (NGS) for analysis.
- C. You boot the failed controller, carry out a giveback, and wait until the issue reoccurs.
- D. You boot the failed controller to maintenance mode and execute the `shdiag` command.

Correct Answer: AB

QUESTION 4

Click the Exhibit tab.



```
::> node run -node node2 ifstat ela
-- interface ela (13 days, 22 hours, 41 minutes, 31 seconds) --


RECEIVE

Frames/second: 39 | Bytes/second: 9956 | Errors/minute: 0
Discards/minute: 0 | Total frames: 37211k | Total bytes: 6257m
Total errors: 0 | Total discards: 0 | Multi/broadcast: 451k
No buffers: 0 | Non-primary u/c: 0 | L2 terminate: 0
Tag drop: 0 | Vlan tag drop: 0 | Vlan untag drop: 0
Vlan forwards: 0 | All pkts: 37238k | MCast pkts: 442k
BCast pkts: 9155 | CRC errors: 298943245 | Bus overrun: 0
Alignment errors: 0 | Long frames: 0 | Jabber: 0
Pause frames: 0 | Runt frames: 0 | Jumbo frames: 176k
All pkts: 26033k | MCast pkts: 20079 | BCast pkts: 940
Bus underruns: 0 | Pause frames: 0 | Jumbo frames: 703k

TRANSMIT

Frames/second: 31 | Bytes/second: 9316 | Errors/minute: 0
Discards/minute: 0 | Total frames: 26030k | Total bytes: 8434m
Total errors: 0 | Total discards: 0 | Multi/broadcast: 21020
Queue overflows: 0 | No buffers: 0

LINK_INFO
Current state: up | Up to downs: 2 | Speed: 10000m
Duplex: full | Flowcontrol: none
```



A customer receives "CLUSTER NETWORK DEGRADED" AutoSupport messages from this clustered Data ONTAP system. The customer suspects that something occurred physically to the nodes after they had a data center maintenance

move. The customer proceeds to follow the instructions in the Knowledge Base article regarding the "Error:

CLUSTER NETWORK DEGRADED" message that results in the output shown in the exhibit. After analysis, the customer decides to replace the small form-factor pluggable (SFP) transceivers and the cables on the system.

Which statistic supports the customer's analysis?

- A. BCast pkts
- B. CRC errors
- C. Jumbo frames
- D. Multi/broadcast

Correct Answer: B

QUESTION 5

Click the Exhibit tab.



```
FILER01:
Sat Mar 12 11:28:12 CET [filer01:cf.rv.notConnected:error]: HA interconnect: Connection for
'cfo_rv' failed.
Sat Mar 12 11:28:12 CET [filer01:rv.connection.torndown:info]: HA interconnect: cfo_rv1 is torn
down on NIC 1.
Sat Mar 12 11:28:12 CET [filer01:cf.rv.notConnected:error]: HA interconnect: Connection for
'cfo_rv1' failed.
Sat Mar 12 11:28:12 CET [filer01:rv.connection.torndown:info]: HA interconnect: cfo_rv2 is torn
down on NIC 1.
Sat Mar 12 11:28:12 CET [filer01:cf.rv.notConnected:error]: HA interconnect: Connection for
'cfo_rv2' failed.
Sat Mar 12 11:28:19 CET [filer01:bridge.removed:info]: FC-to-SAS bridge site3_3:13.126L0 [ATTO
FibreBridge6500N 1.61] S/N [FB6500N108245] was removed.
Sat Mar 12 11:28:19 CET [filer01:bridge.removed:info]: FC-to-SAS bridge site3_3:5.126L0 [ATTO
FibreBridge6500N 1.61] S/N [FB6500N11508] was removed.
```

```
FILER02:
Sat Mar 12 11:28:12 CET [filer02:cf.rv.notConnected:error]: HA interconnect: Connection for
'cfo_rv' failed.
Sat Mar 12 11:28:14 CET [filer02:rv.connection.torndown:info]: HA interconnect: cfo_rv2 is torn
down on NIC 1.
Sat Mar 12 11:28:14 CET [filer02:rv.connection.torndown:info]: HA interconnect: cfo_rv1 is torn
down on NIC 1.
Sat Mar 12 11:28:14 CET [filer02:cf.rv.notConnected:error]: HA interconnect: Connection for
'cfo_rv2' failed.
Sat Mar 12 11:28:14 CET [filer02:cf.rv.notConnected:error]: HA interconnect: Connection for
'cfo_rv1' failed.
Sat Mar 12 11:28:17 CET [filer02:bridge.removed:info]: FC-to-SAS bridge site1_2:13.126L0 [
FibreBridge6500N 1.61] S/N [FB6500N108709] was removed.
Sat Mar 12 11:28:17 CET [filer02:bridge.removed:info]: FC-to-SAS bridge site1_2:5.126L0 [
FibreBridge6500N 1.61] S/N [FB6500N105093] was removed.
```



Your customer's MetroCluster controllers have generated AutoSupport notifications with a "DISK REDUNDANCY FAILED" message. Referring to the exhibit, which component is causing the problem?

- A. the SAN switch site3_3
- B. the SAN switch site1_2
- C. the ATTO bridges on site3
- D. the inter-switch link (ISL) between site1 and site3

Correct Answer: D

[Latest NS0-191 Dumps](#)

[NS0-191 PDF Dumps](#)

[NS0-191 Exam Questions](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.lead4pass.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.
All trademarks are the property of their respective owners.
Copyright © lead4pass, All Rights Reserved.