

NS0-194^{Q&As}

NetApp Certified Support Engineer

Pass NetApp NS0-194 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-194.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

You observe cyclic redundancy check (CRC) errors on a network port from a node in the cluster.

Which two components would you consider reseating or replacing before you perform actions on the physical port where the errors are reported from the node? (Choose two.)

- A. SFP
- B. cluster interconnect switch
- C. up-stream switch
- D. cable

Correct Answer: CD Section: (none)

QUESTION 2

You are working on a fabric MetroCluster. After a site failure, the plex starts to resync automatically to the aggregate mirror of Aggr1. The plex now shows a status of resyncing. During this process, you experience a slow resync of the SyncMirror plex.

In this scenario, how do you solve the problem?

- A. Add more disks to the aggregate to add more I/O capacity.
- B. Destroy and re-create plex, then run a baseline sync.
- C. Tune the resync speed by adding a QoS policy and limit the concurrent I/O to the aggregate.
- D. Tune the resync speed using the storage raid-options command.

Correct Answer: C Section: (none)

Reference: <https://library.netapp.com/ecmdocs/ECMP1368831/html/GUID-F3E1536B-0C54-4D4F-B9853D839032234D.html>

QUESTION 3

In ONTAP 9.6, activity on the command line is found in which log?

- A. audit.log
- B. messages.log
- C. command-history.log
- D. mgwd.log

Correct Answer: A Section: (none)

Reference: https://kb.netapp.com/Advice_and_Troubleshooting/Data_Storage_Software/ONTAP_OS/

Overview_of_ONTAP_Logs

QUESTION 4

You received the "CLUSTER ERROR: DISK/SHELF COUNT MISMATCH" AutoSupport message from an ONTAP cluster.

When analyzing this message, which two should be inspected? (Choose two.)

- A. drive paths
- B. IOM firmware
- C. drive firmware
- D. SAS cabling

Correct Answer: AC Section: (none)

QUESTION 5

A customer asks what is the correct way to configure an ONTAP system for multi-tenancy. The customer wants to serve data and also protect data using SnapMirror from tenant A using network A and from tenant B using network B.

In this scenario, which statement is correct?

- A. The customer must use different VLANs for the two tenants.
- B. This setup can only work if tenant A and tenant B use a shared network infrastructure.
- C. The customer must set up two different IPspaces for the two tenants.
- D. Each node can only communicate with tenant A or tenant B, but not with both at the same time.

Correct Answer: B Section: (none)

[NS0-194 VCE Dumps](#)

[NS0-194 Practice Test](#)

[NS0-194 Study Guide](#)