

## NS0-502<sup>Q&As</sup>

NetApp Certified Implementation Engineer-SAN and Virtualization

### Pass Network Appliance NS0-502 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-502.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Network Appliance Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

for access to a VMFS datastore created on a NetApp LUN on an ESX 4.0 system for an ALUA configuration, the path selection policy should be set to:

- A. MRU (Most Recently Used)
- B. Fixed
- C. RR (Round Robin)
- D. ALUA

Correct Answer: C

---

## QUESTION 2

You need to gather information from the host systems that will be attached to the NetApp storage system using either FC or iSCSI. This information includes operating system version, patch levels, open bus slots, and cards in bus slots.

What other information must you gather from the host systems?

- A. bus type (PCIe and/or PCI-x) and video adapters
- B. memory in system and Ethernet ports (both used and free)
- C. bus type (PCIe and/or PCI-x) and Ethernet ports (both used and free)
- D. bus type (PCIe and/or PCI-x) and Serial ports (both used and free)

Correct Answer: C

---

## QUESTION 3

Which command will display which Brocade switches are connected into a fabric?

- A. fabricshow
- B. switchshow
- C. show fabric
- D. configshow

Correct Answer: A

---

## QUESTION 4

Which components must you configure when configuring CHAP to be used with iSCSI?

- A. host, Ethernet switch, storage controllers
- B. host and storage controllers only
- C. host only
- D. storage controllers only

Correct Answer: B

---

## QUESTION 5

When building your implementation plan, providing dual power for all systems is critical.

Which three actions should be mandated? (Choose three.)

- A. Dual power supplies should be placed in all equipment.
- B. Dual power feeds should be run to all equipment.
- C. Power feeds should be connected to the closest available outlet inside the cabinet.
- D. Power feeds should be connected to separate circuits on the same data center PDU.
- E. Power feeds should be connected to separate outlets connected to two separate PDUs.

Correct Answer: ABE

[NS0-502 Practice Test](#)

[NS0-502 Study Guide](#)

[NS0-502 Braindumps](#)