

# NS0-502<sup>Q&As</sup>

NetApp Certified Implementation Engineer-SAN and Virtualization

## Pass Network Appliance NS0-502 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-502.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Network Appliance Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

A company has deployed a NetApp dual controller FAS3100 series with iSCSI. Currently, there are five Windows servers and three Novell NetWare servers connected to the IP SAN. The customer wants to connect an HP-UX server to the IP SAN.

Which cfmode allows all operating systems to co-exist in the IP SAN?

- A. single\_image
- B. standby
- C. cfmode not applicable
- D. dual\_fabric

Correct Answer: C

---

## QUESTION 2

When setting up a VLAN for administrative security purposes, which four ports are the only important ports to include in the VLAN? (Choose four.)

- A. Storage Controllers Management Ethernet ports
- B. FC Switches Ethernet port
- C. Hosts iSCSI HBA Ethernet port
- D. Ethernet Switches Management port
- E. Storage Controller iSCSI Ethernet Target ports
- F. Hosts NIC Ethernet port

Correct Answer: ABDF

---

## QUESTION 3

Which option needs to be set on a LUN to guarantee that it cannot be affected by other LUNs in the volume?

- A. Volume Guarantee
- B. Volume Space Reserved
- C. LUN Reservation Disabled
- D. LUN Reservation Enabled

Correct Answer: D

---

#### QUESTION 4

When planning for fault tolerant power connections, how should each device to be connected?

- A. with a single power feed
- B. with dual power feeds
- C. with dual power feeds connected to separate outlets
- D. with dual power feeds connected to separate circuits

Correct Answer: D

---

#### QUESTION 5

What is NetApp's recommended best practice for zone configuration?

- A. All zones should contain a single initiator and all the targets that initiator accesses.
- B. Individual zones can get too complicated. It is better to simply configure one default zone with all devices contained in it.
- C. All devices from the same vendor should be in one zone.
- D. All zones should contain a single target and all the initiators using that target.

Correct Answer: A

[Latest NS0-502 Dumps](#)

[NS0-502 Practice Test](#)

[NS0-502 Study Guide](#)