

## NS0-505<sup>Q&As</sup>

NetApp Certified Implementation Engineer – SAN ESeries

### Pass NetApp NS0-505 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-505.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



## QUESTION 1

The ability of many E-Series controllers to hold an additional firmware image in reserve \_\_\_\_\_. (Choose the best answer.)

- A. is used to store a backup boot image
- B. allows controller firmware to be downloaded immediately and activated at a later time
- C. allows two firmware images to be used at the same time
- D. is used for Support use only

Correct Answer: C

---

## QUESTION 2

In the storage manager client, what are host groups? (Choose the best answer.)

- A. A set of I/O hosts with access to the same set of volumes.
- B. Two or more servers that host localcache.
- C. Two or more disk devices joined together
- D. A custom group of virtual machine hosts
- E. Volumes linked to update at the same time

Correct Answer: D

---

## QUESTION 3

The interval for an asynchronous mirror group should usually be equal to \_\_\_\_\_. (Choose the best answer.)

- A. the corresponding application's RPO
- B. half the corresponding application's RPO
- C. half the corresponding application's RTO
- D. the corresponding application's RTO
- E. the amount of time required to copy the size of the mirror repository to the remote site

Correct Answer: E

---

## QUESTION 4

Consult the \_\_\_\_\_ to determine the current link status of a host port. (Choose the best answer.)

- A. Storage Array Profile
- B. Real-time performance monitor
- C. Recovery Guru
- D. Unreadable Sectorslog

Correct Answer: A

---

## QUESTION 5

What is a best practice recommendation for the automated system monitor? (Choose the best answer.)

- A. It should only run on one client connected to the storage system.
- B. It should be stopped during storage system normal operations.
- C. It should be stopped during a controller firmware upgrade.
- D. It should only be run on Windows server systems.
- E. It should run on all storage manager clients.

Correct Answer: C

[Latest NS0-505 Dumps](#)

[NS0-505 Study Guide](#)

[NS0-505 Exam Questions](#)