

## NS0-515<sup>Q&As</sup>

NetApp Certified Implementation Engineer - SAN, E-Series

### Pass NetApp NS0-515 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-515.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

Which three factors should you consider before you install an E2860 in a data center? (Choose three.)

- A. current draw
- B. heat dissipation
- C. fire suppression capacity
- D. electromagnetic interference
- E. ambient temperatures

Correct Answer: CBE

## QUESTION 2

Click the Exhibit button.

Supported Adapter Cards – E2812 Duplex 16Gb 10GbE Base-T 11.50 SANtricity OS							
Adapters							
Priority	Category	Bus Type	Mktg Part No	Images	LED	Mfg Part No	Description
1	Block Access	PCIe2	X-56023-00-0E-C		View		HIC.E2800.10Gb Base-T.2-ports, -C
2	Block Access	PCIe2	X-56026-00-0E-C		View		HIC.E2800.12Gb SAS.2-ports, -C
3	Block Access	PCIe2	X-56027-00-0E-C		View		HIC.E2800.12Gb SAS.4-ports, -C

You ordered a NetApp E2812 Duplex 16GB 10 GbE Base-T system. Referring to the exhibit, what is the maximum number of 10GbE Base-T ports available to be used?

- A. 8
- B. 4
- C. 6
- D. 12

Correct Answer: B

## QUESTION 3

An orphaned volume occurs during an asynchronous mirror implementation. You must recover the orphaned volume.

In this scenario, which statement is correct?

- A. Remove the mirroring relationship on the orphan, then re-create the mirroring relationship
- B. Suspend mirroring operations on the orphan, then resume operations
- C. Deactivate the mirror consistency group that contains the orphan, then re-enable the group
- D. Perform a role change on the orphan, then re-create the mirroring relationship

Correct Answer: A

Reference: [https://library.netapp.com/ecm/ecm\\_download\\_file/ECMP1394847](https://library.netapp.com/ecm/ecm_download_file/ECMP1394847)

---

#### QUESTION 4

What is represented by the Headroom graph on the SANtricity System Manager performance tab?

- A. the percentage of I/O associated with the backend disk drives
- B. the remaining performance capability of the physical objects in the storage system
- C. the percentage of CPU processing capacity that is being used by the operations on the system
- D. the resources that are being consumed by a defined workload

Correct Answer: B

Reference: [https://mysupport.netapp.com/NOW/public/eseries/sam\\_archive1130/GUID-8538272A-B80249D9-9EA2-96C82DAD26A2/GUID-8538272A-B802-49D9-9EA2-96C82DAD26A2\\_2.pdf](https://mysupport.netapp.com/NOW/public/eseries/sam_archive1130/GUID-8538272A-B80249D9-9EA2-96C82DAD26A2/GUID-8538272A-B802-49D9-9EA2-96C82DAD26A2_2.pdf) (379)

---

#### QUESTION 5

You are setting up asynchronous mirroring between two E2860 systems.

In this scenario, which two prerequisites are required to complete the setup? (Choose two.)

- A. Both the primary and secondary systems must be using the same subnets for mirroring connections.
- B. Both the primary and secondary systems must have the same premium features licensed.
- C. Both systems must be discovered by an Enterprise Management Window (EMW) or SANtricity Unified Manager.
- D. The secondary system must have 2X the storage capacity of the primary system.

Correct Answer: BC

[NS0-515 VCE Dumps](#)

[NS0-515 Study Guide](#)

[NS0-515 Braindumps](#)