

NSE7_SDW-7.0^{Q&As}

Fortinet NSE 7 - SD-WAN 7.0

Pass Fortinet NSE7_SDW-7.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/nse7_sdw-7-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibits.

The screenshot shows the FortiGate configuration interface. The top section displays the 'Aggregate' configuration for 'fortilink' and its associated physical interfaces (port1 through port10). The 'Access' column for 'fortilink' is set to 'PING'. The 'Virtual Domain' is 'root' and the 'Administrative Status' is 'Up'. Below this, a 'Tunnel' configuration for 'ssl.root' is shown with 'Manual' addressing mode and 'root' virtual domain. The bottom section shows 'Static Route' configurations for two routes:

ID	Destination	Gateway	Interface	Distance	Priority	Status	Description
1	0.0.0.0/0.0.0.0	10.200.1.254	port1	10	0	Enable	
2	0.0.0.0/0.0.0.0	10.200.2.254	port2	10	0	Enable	

The screenshot shows the FortiGate configuration interface for firewall policies. It displays two policies:

#	Name	From	To	Source	Destination	Schedule	Service	Users	Action	Security Profiles	Log	NAT	Install On	Created Time	Last Modified
1	Internet_Access	port3	port1	all	all	always	ALL		Accept	no-inspection	Log Security Events	Enabled	Installation Targets	2020-10-23 01:46:20	admin/2020-10-23 01:46:20
2	Implicit Deny	any	any	all	all	always	ALL		Deny		No Log		Installation Targets		

ExhibitA shows the system interface with the static routes and exhibit B shows the firewall policies on the managed FortiGate.

Based on the FortiGate configuration shown in the exhibits, what issue might you encounter when creating an SD-WAN zone for port1 and port2?

- A. port2 is referenced in a static route.
- B. port1 is assigned a manual IP address.
- C. port1 and port2 are not administratively down.
- D. port1 is referenced in a firewall policy.

Correct Answer: D

QUESTION 2

Which two statements about SLA targets and SD-WAN rules are true? (Choose two.)

- A. Member metrics are measured only if an SLA target is configured.

B. SLA targets are used only by SD-WAN rules that are configured with Lowest Cost (SLA) or Maximize Bandwidth (SLA) as strategy.

C. When configuring an SD-WAN rule, you can select multiple SLA targets of the same performance SLA.

D. SD-WAN rules use SLA targets to check if the preferred members meet the SLA requirements.

Correct Answer: BD

QUESTION 3

Which two statements are correct when traffic matches the implicit SD-WAN rule? (Choose two.)

A. The `sdwan_service_id` flag in the session information is 0.

B. All SD-WAN rules have the default setting enabled.

C. Traffic does not match any of the entries in the policy route table.

D. Traffic is load balanced using the algorithm set for the `v4-ecmp-mode` setting.

Correct Answer: AC

QUESTION 4

Refer to the exhibit.

```
branch1_fgt # diagnose sys sdwan service 3

Service(3): Address Mode(IPV4) flags=0x200 use-shortcut-sla
  Gen(5), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(priority), link-cost-
factor(latency), link-cost-threshold(10), health-check(VPN_PING)
  Members(3):
    1: Seq_num(3 T_INET_0_0), alive, latency: 101.349, selected
    2: Seq_num(4 T_INET_1_0), alive, latency: 151.278, selected
    3: Seq_num(5 T_MPLS_0), alive, latency: 200.984, selected
  Src address(1):
    10.0.1.0-10.0.1.255

  Dst address(1):
    10.0.0.0-10.255.255.255

branch1_fgt (3) # show
config service
  edit 3
    set name "Corp"
    set mode priority
    set dst "Corp-net"
    set src "LAN-net"
    set health-check "VPN_PING"
    set priority-members 3 4 5
  next
end
```

The exhibit shows the SD-WAN rule status and configuration.

Based on the exhibit, which change in the measured latency will make T_MPLS_0 the new preferred member?

- A. When T_INET_0_0 and T_MPLS_0 have the same latency.
- B. When T_MPLS_0 has a latency of 100 ms.
- C. When T_INET_0_0 has a latency of 250 ms.
- D. When T_MPLS_0 has a latency of 80 ms.

Correct Answer: D

QUESTION 5

Refer to the exhibit.

```
FortiGate # diagnose firewall shaper per-ip-shaper list
name FTP_5M
maximum-bandwidth 625 KB/sec
maximum-concurrent-session 5
tos ff/ff
packets dropped 65
bytes dropped 81040
addr=10.1.0.1 status: bps=0 ses=1
addr=10.1.0.100 status: bps=0 ses=1
addr=10.1.10.1 status: bps=1656 ses=3
```

Which are two expected behaviors of the traffic that matches the traffic shaper? (Choose two.)

- A. The traffic shaper limits the bandwidth of each source IP address to a maximum of 625 KB/sec.
- B. The number of simultaneous connections among all source IP addresses can exceed 5 connections.
- C. The number of simultaneous connections allowed for each source IP address can exceed 5 connections.
- D. The traffic shaper limits the combined bandwidth of all connections to a maximum of 5 MB/sec.

Correct Answer: AB

[Latest NSE7_SDW-7.0 Dumps](#)

[NSE7_SDW-7.0 Practice Test](#)

[NSE7_SDW-7.0 Study Guide](#)