PW0-104 Q&As

Wireless LAN Administration Exam

Pass CWNP PW0-104 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.lead4pass.com/PW0-104.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

The IEEE 802.11-2007 standard requires ERP capable devices to be backward compatible with devices using which other 802.11 physical layer specifications (PHYs)? (Choose two)

A. DSSS

B. FHSS

C. HR/DSSS

D. ERP-PBCC

E. DSSS-OFDM

Correct Answer: AC

QUESTION 2

Given:

ABC Company has hired you to perform an indoor site survey of their 7-story facility. ABC Company owns the building and rents out unused floors (floors 2 and 4) to other companies, and the other companies use 802.11 WLANs already.

ABC Company wants all of the offices they occupy to be surveyed as part of the project.

What actions should be recommended as part of the site survey project? (Choose two)

A. Verify that RF signals from ABC\\'s APs are not penetrating outside the perimeter of the building.

B. Determine how much signal strength is bleeding between floors.

C. Locate wiring closets on each floor occupied by ABC Company.

D. Identify security best practice violations on neighboring WLANs.

E. Verify that ABC\\'s APs are not directly above or below APs on adjacent floors.

Correct Answer: BC

QUESTION 3

What term correctly completes the following sentence?

In an IEEE 802.11 frame, the IP packet is considered by the MAC layer to be a(n) _____.

A. MAC Service Data Unit (MSDU)

B. MAC Protocol Data Unit (MPDU)

C. Bridge Protocol Data Unit (BPDU)

D. PLCP Service Data Unit (PSDU)

E. PLCP Protocol Data Unit (PPDU)

Correct Answer: A

QUESTION 4

What statement about 802.11 WLAN performance is true?

A. Use of larger frame sizes results in greater throughput in low interference environments.

B. BSS support for 65 KB A-MPDUs will increase the maximum data rate available to client devices.

C. In 802.11n, changing the security mechanism from WPA2-Personal to WPA2-Enterprise will enable the HT MCS rates.

D. Compared to an Independent BSS, an Infrastructure BSS can provide almost twice the throughput between wireless nodes.

E. Use of short guard intervals improves reliability and throughput in high multipath environments

Correct Answer: A

QUESTION 5

What causes of hidden nodes within a BSS would likely lead to an increase in collisions and retries? (Choose two)

A. Data frames too large for the physical environment

B. Client stations broadcasting with too much power

C. Access points broadcasting with too little power

D. Client stations too close in proximity to each other

E. Obstacles between client stations causing attenuation

F. Large 802.11 cells with physically distributed stations

Correct Answer: EF

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: