

# PW0-105<sup>Q&As</sup>

Certified Wireless Network Administrator (CWNA)

## Pass EC-COUNCIL PW0-105 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/pw0-105.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EC-COUNCIL Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which features are incorporated in the 802.11-2007 specification and are recommend for robust WLAN client security?  
(Choose 2)

- A. SSID hiding
- B. CAPWAP with DTLS
- C. 802.1X/EAP
- D. CCMP cipher suite
- E. IPsec VPN
- F. MAC address whitelists

Correct Answer: CD

---

**QUESTION 2**

Given: You have been sent as a consultant to a customer site that is experiencing problems with some 2.4 GHz clients on their 802.11a/g network. After collecting information from the company about the problem, your initial troubleshooting step is to find a client device experiencing performance problems and observe its

802.11 frame exchanges in a protocol analyzer. The retransmission rate for that client is 65% instead of the company's baseline, which is 9%.

Based on this information, what troubleshooting step should follow to isolate the problem?

- A. Check the frame decodes in the protocol analyzer and look for an excessive number of deauthentication frames.
- B. Evaluate the client's operating frequency band with a spectrum analyzer, looking for a high noise floor or interference sources.
- C. Utilize a laptop-based site survey and planning tool to create a predictive model of the optimal AP placement in the customer's facility.
- D. With a protocol analyzer, identify the client's roaming threshold settings and reassociation behavior.
- E. Install Wi-Fi endpoint security and reporting software on the client device to monitor and log the retransmission behavior.

Correct Answer: B

---

**QUESTION 3**

Given: As a station moves away from the access point to which it is associated, it changes its data rate from 54 Mbps to 48 Mbps and then to 36 Mbps.

What IEEE 802.11 term is used to describe this functionality?

- A. Dynamic Rate Switching
- B. Multirate Control
- C. Modulation and Coding Selection
- D. Rate Set Selectivity
- E. Adaptive Rate Management

Correct Answer: A

---

#### QUESTION 4

ABC Company has just purchased a 6 dBi patch antenna. After performing some tests with the 6 dBi antenna, they have concluded that more antenna gain is needed to cover their outdoor courtyard. When choosing an antenna with higher gain, what other antenna characteristic will also change?

- A. Fresnel Zone size
- B. Maximum input power
- C. Beamwidth
- D. Impedance
- E. VSWR Ratio

Correct Answer: C

---

#### QUESTION 5

Given: You are on-site to perform a post-deployment site survey. When verifying a multiple channel VoWiFi deployment using a VoWiFi handset, which aspect is most important?

- A. Performing protocol analysis with a single wireless adapter that is scanning all channels in use
- B. Testing a constant conversation or handset tone while roaming from area to area, or performing an active survey
- C. Configuring DSCP-to-802.11e QoS maps on the handset for each access category.
- D. Verifying the orientation/polarity of all omni-directional antennas in use by the VoWiFi clients.

Correct Answer: B

[PW0-105 PDF Dumps](#)

[PW0-105 Exam Questions](#)

[PW0-105 Brainsdumps](#)