

QSA2018^{Q&As}

Qlik Sense Data Architect Certification Exam

Pass Qlik QSA2018 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/qsa2018.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Qlik Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibits.

Region
Region.ID
Region
EmployeeID
Sales

▼ Preview

Region		Preview of data			
Region.ID	Region	EmployeeID	Sales		
1	North	-	-		
2	West	-	-		
4	South	-	-		
5	-	-	-		
1	-	111	100		
1	-	222	50		
1	-	333	150		

App1 | Edit | Sheet1 | No selections applied | IQ Insights

Sheet1

Region	Region.ID	Sum(Sales)
Totals		1425
North	1	0
South	4	0
West	2	0
-	1	300
-	2	225
-	3	200
-	4	300
-	5	0
-	-	400

Executives need to see the total sales by region for the current year. The data architect inherits App1 from the former employee who tries to address this requirement. Two Microsoft Excel spreadsheets, Region and Employee, are used as the data source. The data architect creates a table and identifies errors in the amount of sales per region.

Which method should the data architect use to resolve the errors?

- A. In the data manager, split the region table and associate by EmployeeID
- B. In the data manager, concatenate the Region table and associate by Region.ID
- C. In the data load editor, concatenate the region and Employee tables
- D. In the data manager, split the region table and associate by Region.ID

Correct Answer: D

QUESTION 2

Refer to the exhibit.

Name	Country
Bob	USA
John	US
Fred	U.S.A.
Amy	France

The Country field in a CRM app is a free-form text field. More spelling variations and countries are expected in the future. A data architect must create a field called CountryCode based on the value in the Country field.

Which script should the data architect create to perform this task?

- A. `LOAD Name,
Pick(Match(Country, 'USA', 'US', 'U.S.A.', 'France'), 'USA', 'USA', 'USA', 'FRA') AS CountryCode;`
- B. `CountryCode:
MAPPING LOAD * INLINE [
Country, CountryCode
USA, USA
US, USA
U.S.A., USA
France, FRA
];

Persons:
LOAD Name,
ApplyMap('CountryCode', Country, 'UNK') AS CountryCode;`
- C. `LOAD Name,
If (Left(Country,1)='U', 'USA', 'FRA') AS CountryCode;`
- D. `CountryCode:
LOAD * INLINE [
Country, CountryCode
USA, USA
US, USA
U.S.A., USA
France, FRA
];

Persons:
JOIN LOAD Name,
Country;`

A. B. C. D.

Correct Answer: B

QUESTION 3

Refer to the exhibit.

```
LIB CONNECT TO 'SQL (abc_qservice)';

OrderHeader:
LOAD CustomerID,
    EmployeeID,
    OrderDate,
    OrderID;
SQL SELECT CustomerID,
    EmployeeID,
    OrderDate,
    OrderID
FROM orders;

OrderData:
LOAD
    OrderID,
    OrderSalesAmount
FROM [lib://QVD (abc_qservice)/OrderData.qvd]
(qvd);

OrderDetail:
LOAD LineNo,
    OrderID,
    ProductNumber,
    Price;
SQL SELECT *
FROM orderdetails;
```

An existing app on Qlik Sense Enterprise is duplicated and transferred to a data architect to add some additional data. When trying to manually reload the original script, the data architect receives an error.

What should be done to make sure the script runs correctly?

- A. Add the line LIB CONNECT TO `SQL (abc_qservice)` before the LOAD for the OrderDetail table.
- B. Give the data architect the Read rights on the data connections in the QMC.
- C. Make the data architect the owner of the app in the QMC.
- D. Add the LIB CONNECT TO `QVD (abc_qservice/OrderData.qvd)` before the LOAD for the OrderData table.

Correct Answer: A

QUESTION 4

Refer to the exhibit.

Sales:

LOAD

```
EmployeeID,  
Sales,  
Division,  
"Business Family",  
"Customer Type",  
Channel,  
"Category Code 5",  
"Zone Mgr",  
"Category Code 7",  
"Regional Sales Mgr"
```

FROM

```
[D:\Employee\Data\Sales.qvd]  
(qvd);
```

Qualify;

Join

LOAD

```
EmployeeID,  
Target
```

FROM

```
[D:\Employee\Data\Target.qvd]  
(qvd);
```

Unqualify;

A QlikView app was converted to a Qlik Sense app using the Dev Hub converter.

The new Qlik Sense app was reloaded without editing the script or the server settings, which created a script error.

What should a data architect do to resolve the issue?

- A. Delete the Qualify statement
- B. Add fields to the Qualify statement
- C. Use a folder connection
- D. Check the QVDs

Correct Answer: C

QUESTION 5

Refer to the exhibits.

CatID	Value
0A8A1DA5-AA23-C713-CB2A-83CABA5FD517	189
1C5B14DF-B613-10D2-DBCFC8FA535F059C	316
03A0D34F-F7DA-AE7F-C1B0-392531DC42DB	704
4B8496DA-B5B6-7F74-3BC9-076EA855A570	327
5A4AC55E-AE0C-0432-344A-2F7B8E7CC066	888
5A30CE40-2B91-B114-0DA4-3144C1DF37E3	371
5B80F7B7-A730-5C8F-932F-9E22BB77D43E	-
9E8495EB-9DB0-C80A-709B-CA2DC3E6224E	596
26C4AEF9-E8D2-3E87-00E7-6251CD4513FE	924
042A4655-D3EC-3758-42B0-6046069F3BB3	639
58C38173-DD6A-BADB-2670-494612A8D38A	-
60BDE857-72EF-93AE-6F39-6FF551F1A420	-
70007000-0000-0000-0000-000000000000	700

```
LIB CONNECT TO 'DemoCORP SQL Server';
```

Values:

```
LOAD
```

```
    CatID,
```

```
    Value
```

```
FROM SalesDB.AgregatedValues;
```


```
left join
```

```
LOAD
```

```
    CatID,
```

```
    ProdID
```

```
FROM SalesDB.Categories;
```



Values
CatID
Value
ProdID

Value	
Density	100%
Subset ratio	100%
Has duplicates	true
Total distinct values	28
Present distinct values	28
Non-null values	31

Business analytics report data issues in the Value field of a table since the latest reload of the data.

What causing this issue?

- A. Null values in the source data
- B. Hyphen characters ('-') in the source data
- C. Pre-aggregated data is being used
- D. Some categories do NOT exist in the Category table

Correct Answer: A

[Latest QSDA2018 Dumps](#)

[QSDA2018 VCE Dumps](#)

[QSDA2018 Braindumps](#)