

VCS-260^{Q&As}

Administration of Veritas InfoScale Availability 7.3 for UNIX/Linux

Pass Veritas VCS-260 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/vcs-260.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Veritas
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

An administrator wants to deploy a complex cluster configuration that will include over six nodes, I/O fencing, and multiple private cluster interconnections.

Which method will help the administrator to implement rapid cluster deployment?

- A. prepare a custom main.cf file using the sample template files and copy the file to all cluster nodes
- B. generate a custom installation script using the Veritas Services and Operations Readiness Tools (SORT) website
- C. prepare a custom response file in Veritas InfoScale Operations Manager (VIOM) and push it out to the new cluster
- D. prepare a custom response file to build the new cluster configuration using /opt/VRTS/install/installer

Correct Answer: D

QUESTION 2

What is the purpose of the AutoClearLimit attribute?

- A. It defines the number of attempts to clear the Faulted state of a resource on all nodes.
- B. It defines the number of attempts to clear the Faulted state of a service group on all nodes.
- C. It defines the number of attempts to clear the AutoDisabled state of a service group on a node.
- D. It defines the number of attempts to clear the Faulted state of a resource on a single node.

Correct Answer: B

QUESTION 3

An administrator receives the following message:

```
"hastatus -sum" shows
-- AGENTS FAILED
-- Type      System
I Application  node01
```

Which command should the administrator run to recover from the failure?

- A. hastart
- B. harecover
- C. haagent

D. hatype

Correct Answer: A

QUESTION 4

A cluster configured with disk based I/O fencing has two dedicated high-priority LLT links and one low-priority link over public network interface.

What is the state of the cluster if both high-priority links fail simultaneously?

- A. All nodes remain in regular GAB membership, but are also in jeopardy membership.
- B. The cluster is in a split-brain condition until at least one other LLT link is working.
- C. The cluster with active service groups stays running, but the other shuts down.
- D. Service groups are unable to failover when resource faults occur, but can failover if a system fault occurs.

Correct Answer: B

QUESTION 5

Which command should an administrator use to generate an encrypted password for editing a resource in the main.cf file?

- A. vcsencrypt -vcs
- B. hares -modify
- C. vcsencrypt -agent
- D. hatype -modify

Correct Answer: C

[Latest VCS-260 Dumps](#)

[VCS-260 VCE Dumps](#)

[VCS-260 Exam Questions](#)