

VCS-260^{Q&As}

Administration of Veritas InfoScale Availability 7.3 for UNIX/Linux

Pass Veritas VCS-260 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/vcs-260.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Veritas
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which two requirements must be met to allow an administrator to configure LLT heartbeats over UDP? (Choose two.)

- A. The LLT private links must be on the same subnet.
- B. Each NIC must have an IP address configured before configuring LLT.
- C. LLT must be configured in the same subnet.
- D. Each link must have a unique UDP port.
- E. Broadcast must be enabled for the heartbeat subnet.

Correct Answer: BD

QUESTION 2

As part of the consolidation efforts in a data center, the administrator decides to merge two two-node Veritas Cluster Server (VCS) clusters into a four-node VCS cluster. The source and target clusters are on the same networks for LLT communication. The administrator performs the following task as preparation for the merge while both clusters are still running:

1.
modifies `/etc/llttab` files on the source cluster systems so the cluster ID is changed to the cluster ID of the target cluster
2.
modifies `/etc/llthosts` files on all systems to include the four nodes
3.
modifies `/etc/gabtab` files on all systems to require four systems to seed
4.
ensures the source cluster systems can see the fencing disks used by the target cluster
5.
copies the fencing configuration files from the target cluster systems to the source cluster systems
6.
adds the source cluster systems to the target cluster configuration using the `hasys -add` command

After the preparation is complete, the administrator stops the source cluster leaving the applications running, then stops the whole communication stack and restarts it in the correct order. When the administrator attempts to start the cluster again on the source cluster systems, they fail to join the four-node cluster.

Which preparation step that the administrator failed to perform is preventing the source cluster systems from joining the four-node cluster?

- A. The cluster needs to be manually seeded using `gabconfig -x` on the source cluster systems.
- B. The target `main.cf` file needs to be copied to the source cluster systems.
- C. The service group configuration of the source cluster needs to be applied to the target cluster.
- D. The cluster UUID from the target cluster needs to be copied to the source cluster.

Correct Answer: D

QUESTION 3

Which resource type can an administrator use to mirror the state of another persistent resource?

- A. Phantom
- B. Proxy
- C. VolumeSet
- D. NotifierMngr

Correct Answer: B

QUESTION 4

Refer to the exhibit.

How many services are seeded in the GAB port membership?

GAB status and membership notation

```
# gabconfig -a
GAB Port Memberships
=====
Port a gen f7c001 membership 01 ;
Port b gen f7c004 membership 01 ;
Port h gen f7c002 membership 01 ;
```

- A. The GAB port membership has two nodes: 1 and 2.
- B. The GAB port membership has three nodes: 0, 1, and 12.
- C. The GAB port membership has one node: 1.

D. The GAB port membership has four nodes: 0, 1, 21, and 22.

Correct Answer: D

QUESTION 5

What is the impact to unsaved configuration changes in Veritas Cluster Server when an administrator stops the cluster with a force option from the command-line interface?

- A. The changes are automatically saved.
- B. The changes are automatically discarded.
- C. The potential corruption of the cluster configuration.
- D. The changes are prompted to be discarded.

Correct Answer: D

[Latest VCS-260 Dumps](#)

[VCS-260 Exam Questions](#)

[VCS-260 Braindumps](#)