

# 1Y0-231<sup>Q&As</sup>

Deploy and Manage Citrix ADC 13 with Citrix Gateway

## Pass Citrix 1Y0-231 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/1y0-231.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

Scenario: A Citrix Administrator configured the policies below:

POLICY 1: add rewrite action ACT\_1 corrupt\_http\_header Accept-Encoding add rewrite policy POL\_1 HTTP.REQ.IS\_VALID ACT\_1

POLICY 2:

add rewrite action ACT\_2 insert\_http\_header Accept-Encoding "\"identity\""

add rewrite policy POL\_2 "HTTP.REQ.IS\_VALID" ACT\_2

Which set of commands can the administrator use to bind the rewrite policies to the LB vserver lb\_vsrv so that POL\_2 is evaluated after POL\_1 is evaluated successfully?

- A. bind lb vserver lb\_vsrv -policyName POL\_1 -priority 110 -gotoPriorityExpression NEXT -type REQUEST bind lb vserver lb\_vsrv -policyName POL\_2 -priority 100 -gotoPriorityExpression END -type REQUEST
- B. bind lb vserver lb\_vsrv -policyName POL\_1 -priority 90 -type REQUEST bind lb vserver lb\_vsrv -policyName POL\_2 -priority 100 -type REQUEST
- C. bind lb vserver lb\_vsrv -policyName POL\_1 -priority 90 -gotoPriorityExpression END -type REQUEST bind lb vserver lb\_vsrv -policyName POL\_2 -priority 80 -gotoPriorityExpression NEXT -type REQUEST
- D. bind lb vserver lb\_vsrv -policyName POL\_1 -priority 90 -gotoPriorityExpression NEXT -type REQUEST bind lb vserver lb\_vsrv -policyName POL\_2 -priority 100 -gotoPriorityExpression END -type REQUEST

Correct Answer: A

---

## QUESTION 2

Scenario: A Citrix ADC MPX is using one of four available 10G ports. A Citrix Administrator discovers a traffic bottleneck at the Citrix ADC.

What can the administrator do to increase bandwidth on the Citrix ADC?

- A. Add two more 10G Citrix ADC ports to the network and configure VLAN.
- B. Add another 10G Citrix ADC port to the switch, and configure link aggregation control protocol (LACP).
- C. Purchase another Citrix ADC MPX appliance.
- D. Plug another 10G Citrix ADC port into the router.

Correct Answer: A

---

## QUESTION 3

Scenario: A Citrix Administrator deployed a Citrix ADC in one-arm mode. Currently, the VLANs 20, 30, and 40 are

tagged on the interface with the option of `tagall`.

What is true regarding the VLANs, when `tagall` is enabled on the interface?

- A. VLANs 1, 20, 30, 40, and HA packets are tagged on the interface.
- B. VLANs 20, 30, and 40 are tagged on the interface.
- C. VLANs 1, 20, 30, and 40 are tagged on the interface.
- D. VLANs 20, 30, 40, and HA packets are tagged on the interface.

Correct Answer: C

---

#### QUESTION 4

Scenario: A Citrix Administrator needs to test a SAML authentication deployment to be used by internal users while accessing several externally hosted applications. During testing, the administrator notices that after successfully accessing any partner application, subsequent applications seem to launch without any explicit authentication request.

Which statement is true regarding the behavior described above?

- A. It is expected if the Citrix ADC appliance is the common SAML identity provider (IdP) for all partners.
- B. It is expected due to SAML authentication successfully logging on to all internal applications.
- C. It is expected if all partner organizations use a common SAML service provider (SP).
- D. It indicates the SAML authentication has failed and the next available protocol was used.

Correct Answer: B

---

#### QUESTION 5

A Citrix Administrator needs to integrate an existing certification-based authentication policy into an existing Citrix Gateway virtual server.

Which three steps can the administrator take to accomplish this? (Choose three.)

- A. Bind the existing CERT authentication policy to the Citrix Gateway virtual server.
- B. Enable the two-factor option on the existing CERT authentication profile.
- C. Enable client authentication on the SSL parameters of the virtual server.
- D. Change the client certificate to mandatory on the SSL parameters of the virtual server.
- E. Create a CERT authentication policy and bind it to the Citrix Gateway virtual server.

Correct Answer: CDE

Reference: <https://docs.citrix.com/en-us/citrix-gateway/current-release/authentication-authorization/configure-client-cert-authentication/ng-client-cert-vserver-and-bind-tsk.html>

**QUESTION 6**

Scenario: While attempting to access a web server that is load-balanced by a Citrix ADC using HTTPS, a user receives the message below:

SSL/TLS error: You have not chosen to trust "Certificate Authority" the issuer of the server's security certificate.

What can a Citrix Administrator do to prevent users from getting this message?

- A. Ensure that the server certificate is linked to its respective intermediate and root certificates.
- B. Ensure that users have the server certificate installed.
- C. Ensure that users have the certificate's private key.
- D. Ensure that users have the certificate's public key.

Correct Answer: A

Reference: <https://docs.citrix.com/en-us/citrix-gateway/12-1/citrix-gateway-12.1.pdf>

---

**QUESTION 7**

Scenario: A Citrix Administrator suspects an attack on a load-balancing virtual server (IP address 192.168.100.25). The administrator needs to restrict access to this virtual server for 10 minutes.

Which access control list (ACL) will accomplish this?

- A. `add ns acl rule1 DENY -destIP 192.168.100.25 -TTL 600000`
- B. `add simpleacl rule1 DENY -srcIP 192.168.100.25 -TTL 600000`
- C. `add ns acl rule1 DENY -destIP 192.168.100.25 -TTL 600`
- D. `add simpleacl rule1 DENY -srcIP 192.168.100.25 -TTL 600`

Correct Answer: D

---

**QUESTION 8**

Which scenario will cause automatic high availability (HA) synchronization to fail?

- A. Different build versions
- B. A configuration change to the primary Citrix ADC
- C. A forced failover
- D. Manually forced synchronization

Correct Answer: D

---

Reference: <https://support.citrix.com/article/CTX124439>

---

## QUESTION 9

Scenario: A Citrix Administrator currently manages a Citrix ADC environment for a growing retail company that may soon double its business volume. A Citrix ADC MPX 5901 is currently handling web and SSL transactions, but is close to full capacity. Due to the forecasted growth, the administrator needs to find a cost-effective solution.

Which cost-effective recommendation can the administrator provide to management to handle the growth?

- A. A license upgrade to a Citrix ADC MPX 5905
- B. The addition of another MPX 5901 appliance
- C. A hardware upgrade to a Citrix ADC MPX 8905
- D. A hardware upgrade to a Citrix ADC SDX 15020

Correct Answer: A

---

## QUESTION 10

A Citrix Administrator configured a Citrix Gateway virtual server for authentication, but there is no authentication policy bound to the virtual server.

Which authentication binding point will the Citrix ADC evaluate next?

- A. Override global
- B. Group
- C. Default global
- D. User

Correct Answer: D

---

## QUESTION 11

A Citrix Administrator configured a load-balancing virtual server to utilize the least bandwidth load-balancing method. A service attached to this virtual server is brought into the effective state during production hours.

During the startup of a virtual server, which load-balancing method is used by default?

- A. Round-robin
- B. Least connections
- C. Least bandwidth
- D. Custom load

Correct Answer: B

Reference: <https://support.citrix.com/article/CTX108886>

---

## QUESTION 12

Scenario: While performing a disaster recovery test, a Citrix Administrator decides to failover the Citrix ADC high availability (HA) pair appliances. The administrator notices that the failover is NOT working as expected, and the secondary Citrix ADC is NOT taking over as primary. The administrator suspects that networking issues may be causing the failure.

What could be the cause of this issue?

- A. HA monitoring is enabled on an interface of the secondary node that shows as ENABLED, DOWN.
- B. HA monitoring is enabled on a disabled interface of the primary node.
- C. HA heartbeats are only seen on some enabled interfaces of the secondary node.
- D. The Independent Network Configuration (INC) mode is enabled on the primary node.

Correct Answer: A

---

## QUESTION 13

What does a Citrix Administrator need to configure to allow access to Citrix Virtual Apps and Desktops without the use of a VPN or a clientless-access connection?

- A. Ciphers group
- B. SSL profile
- C. Net profile
- D. ICA proxy

Correct Answer: D

Reference: <https://www.carlstalhood.com/category/netScaler/netScaler-12/netScaler-gateway-12/>

---

## QUESTION 14

Which Citrix Gateway feature should a Citrix Administrator configure to allow traffic for specific iOS applications only?

- A. Full SSL VPN tunnel for iOS
- B. Per app VPN tunnel
- C. Split DNS
- D. SmartControl for iOS

Correct Answer: B

Reference: <https://docs.citrix.com/en-us/citrix-gateway/citrix-gateway-clients/set-up-sso-for-ios-users.html>

---

## QUESTION 15

Scenario: To meet the security requirements of the organization, a Citrix Administrator needs to configure a Citrix Gateway virtual server with time-outs for user sessions triggered by the behaviors below:

Inactivity for at least 15 minutes.

No keyboard or mouse activity for at least 15 minutes

Which set of time-out settings can the administrator configure to meet the requirements?

- A. Session time-out and client idle time-out set to 15
- B. Session time-out and forced time-out set to 15
- C. Client idle time-out and forced time-out set to 15
- D. Client idle time-out and forced time-out set to 900

Correct Answer: A

Reference: <https://docs.citrix.com/en-us/citrix-gateway/current-release/vpn-user-config/configure-pluginconnections/configure-time-out-settings.html>

[Latest 1Y0-231 Dumps](#)

[1Y0-231 PDF Dumps](#)

[1Y0-231 Study Guide](#)