1Y0-A21^{Q&As}

Basic Administration for Citrix NetScaler 9.2

Pass Citrix 1Y0-A21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/1y0-a21.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Citrix Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

😳 365 Days Free Update

Leads4Pass

800,000+ Satisfied Customers



QUESTION 1

Scenario: A network administrator needs to configure routing on a NetScaler appliance. The NetScaler is in a DMZ whose gateway is 10.54.80.1/24. There are no configured routes on the NetScaler.

Given this topology, which is the appropriate routing configuration for the NetScaler?

- A. set default route 10.54.80.1
- B. add route 0.0.0.0 0.0.0.0 10.54.80.1
- C. set default route 0.0.0.0 0.0.0.0 10.54.80.1
- D. add route 0.0.0.0 255.255.255.255 10.54.80.1

Correct Answer: B

QUESTION 2

In which manner can an administrator configure a NetScaler device so that it can load balance external DNS servers?

- A. Configure as an ADNS.
- B. Configure CNAME records.
- C. Configure as a DNS proxy.
- D. Configure as an End resolver.

Correct Answer: C

QUESTION 3

Scenario: A financial company needs to maintain end-to-end security in network traffic. The company also requires that an administrator reduce the CPU levels for back-end servers in their environment because it requires end-to-end security.

Which setting on the SSL virtual server reduces CPU utilization on the back-end?

A. SSLv3

- B. SSL Redirect
- C. SSL Session Reuse
- D. SSL Client Certificates

Correct Answer: C

QUESTION 4

Scenario: An administrator is working with a Citrix consultant to architect and implement a NetScaler solution. They plan to use GSLB and DNS views in the environment.

In which two manners can the administrator configure the NetScaler system to be able to configure DNS views that support GSLB records? (Choose two.)

A. Configure as an ADNS.

B. Configure as a DNS proxy.

C. Configure CNAME records.

D. Configure as an End resolver.

Correct Answer: AB

QUESTION 5

A network administrator wants to ensure that connection multiplexing is enabled for all client connections that hit a virtual server. Which service type should the administrator select to enable connection multiplexing?

A. SSL

B. FTP

C. TCP

D. HTTP

Correct Answer: D

QUESTION 6

Scenario: A company has contracts with multiple ISPs and would like to use all of them for Internet connections although some ISP routers are faster than others. The company also plans to use a NetScaler system for load balancing and failover.

What can an administrator configure to ensure that all ISP connections are being used while avoiding retransmission or out-of-order packets in this environment?

A. Multiple VLANs with Ingress rules

- B. Link load balancing with destination IP-based persistence
- C. Round robin load balancing with reverse RNAT configured
- D. A load balancing policy with the appropriate preferred IP and preferred port parameters configured

Correct Answer: B

QUESTION 7

An administrator wants to configure the virtual server and services so that existing connections stay open when a service is marked down but NOT when a virtual server is marked down.

How must the administrator configure the service and virtual server to reflect this dependency?

A. set Ib vserver Ibv1 -downStateFlush ENABLED set service svc1 -downStateFlush ENABLED

B. set lb vserver lbv1 -downStateFlush DISABLED set service svc1 -downStateFlush ENABLED

C. set lb vserver lbv1 -downStateFlush ENABLED set service svc 1 -downStateFlush DISABLED

D. set lb vserver lbv1 -downStateFlush DISABLED set service svc1 -downStateFlush DISABLED

Correct Answer: C

QUESTION 8

Scenario: An administrator is attempting to force synchronization between two nodes in an HA setup. Once the synchronization is complete, the administrator receives a message.

In order to verify that the synchronization has been successful, the administrator should execute the ______ command. (Choose the correct option to complete the sentence.)

- A. show node
- B. show monitor
- C. show sync status
- D. show system status

Correct Answer: A

QUESTION 9

Scenario: An administrator needs to configure SSL offloading on a NetScaler system. The administrator has already enabled SSL on the NetScaler, added the necessary service and added an SSL-based virtual server.

Which three additional steps must the administrator take to complete the SSL offloading configuration? (Choose three.)

- A. Create load balancing virtual servers.
- B. Bind the created service to the virtual server.
- C. Add a wildcard certificate to the virtual server.
- D. Add an SSL certificate key pair to the NetScaler.
- E. Bind the SSL certificate key pair to the virtual server.
- F. Obtain an SSL certificate from an authorized certificate authority (CA).

Correct Answer: BDE

QUESTION 10

An administrator plans to configure a content filtering policy to drop trace and connect methods.

Which expression should an administrator use in the content filtering policy to explicitly drop trace and connect methods?

A. REQ.HTTP.METHOD != TRACE || REQ.HTTP.METHOD != CONNECT

B. REQ.HTTP.METHOD == TRACE || REQ.HTTP.METHOD == CONNECT

- C. REQ.HTTP.METHOD != TRACE and and REQ.HTTP.METHOD != CONNECT
- D. REQ.HTTP.METHOD == TRACE and and REQ.HTTP.METHOD == CONNECT

Correct Answer: B

QUESTION 11

Which three components does an administrator have to configure in order to establish a basic content switching setup? (Choose three.)

- A. GSLB sites
- B. SSL Offload
- C. ADNS services
- D. Rule or URL-based policies
- E. Load balancing virtual server
- F. Content switching virtual server

Correct Answer: DEF

QUESTION 12

Which command can an administrator use to display the node state in an HA pair?

- A. show ha pair
- B. show ha state
- C. show ha node
- D. show ha primary
- Correct Answer: C

QUESTION 13

Which spillover type should an administrator configure to divert SSL sessions to a backup virtual server once they exceed a specified threshold?

- A. Dynamic
- B. Redirect URL
- C. Bandwidth-based
- D. Connection-based

Correct Answer: D

QUESTION 14

An administrator must first enable the ______ feature before a URL transformation policy can be used in a network environment. (Choose the correct option to complete the sentence.)

A. rewrite

- B. responder
- C. content filtering
- D. URL transformation
- Correct Answer: A

QUESTION 15

Scenario: An administrator needs to satisfy the following conditions:

-The traffic should be encrypted end-to-end

-

There is no certificate configured on the virtual server

Which type of virtual server should the administrator configure on the NetScaler?

Α.

SSL

В.

- TCP
- C.

HTTP

D.

SSL_TCP

Ε.

SSL_BRIDGE

Correct Answer: E

1Y0-A21 PDF Dumps

1Y0-A21 Practice Test

1Y0-A21 Study Guide