

DES-1241^{Q&As}

Specialist - Platform Engineer, PowerStore

Pass Dell DES-1241 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/des-1241.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Dell Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

When looking at the base enclosure front view, what does a solid amber drive LED indicate?

- A. Discover new drive
- B. Rebuild activity
- C. Faulted drive
- D. Normal activity

Correct Answer: C

Reference: <https://www.dell.com/support/kbdoc/en-pk/000125739/powerstore-understanding-led-colors-and-states-for-troubleshooting>

QUESTION 2

What describes Dell EMC PowerStore X front-end cabling?

- A. Uses internal VMware virtual switching and does not require a management network
- B. Storage and management use the same LACP bonded cable connection
- C. Uses VLTi data switch interconnectivity to support vMotion networks
- D. Management and discovery use the same cables and connections as storage

Correct Answer: C

QUESTION 3

A Storage Administrator encounters a Snapshot issue on a Dell EMC PowerStore X system.

The administrator engages support and they determine the Snapshot issue is a known code bug within the OS version of PowerStore code. How can support address the problem in a timely manner?

- A. Disable the Snapshots feature to avoid encountering the code bug
- B. Upgrade the Snapshot portion of code within the OS
- C. Upgrade the PowerStore with a hotfix that corrects the code bug
- D. Wait for a new full OS release that corrects the code bug

Correct Answer: C

QUESTION 4

What is a step in configuring the ToR data switches for a Dell EMC PowerStore X?

- A. Configure a port for the discovery laptop
- B. Create VLANs for NAS servers
- C. Create node A port-channel
- D. Configure LACP uplink to management switch

Correct Answer: B

Reference: <https://www.dell.com/support/manuals/pk/en/pkbsd1/powerstore-9000t/pwrstr-ntwk-cfg/configure-port-interfaces-for-powerstore-x-model-node-connectivity?guid=guid-ef6b40ef-82a3-4ebf-99bf-a7bea8d6a586&lang=en-us>

QUESTION 5

A Storage Administrator ran a PSTCLI command on a Linux host. The error " -bash: pstcli: command not found" appears. How is the problem resolved?

- A. Add the installation directory to the PATH variable on shell initialization file
- B. Install in default directory /opt/dellemc/pstcli-version/bin/
- C. Add /opt/dellemc/pstcli/bin/ in PSTCLI.sh
- D. Run rpm -ihv pstclito reinstall the PSTCLI software on the Linux host

Correct Answer: A

Reference: https://downloads.dell.com/manuals/common/pwrstr-clig_en-us.pdf

QUESTION 6

For what is the "svc_container_mgmt status CP" command used?

- A. Clears the Control Path audit log
- B. Resets the Data Path root access
- C. Checks the status of the Control Path
- D. Checks the status of the Data Path

Correct Answer: C

Reference: <http://webcache.googleusercontent.com/search?q=cache:ZhvW4-xt2TEJ:dunmer.net/guides/powerstore-implementation/PowerStore%252BBasic%252BTroubleshooting%252BExternal%252B-%252BParticipant%252BGuide.pdf+andcd=3andhl=enandct=clnandgl=pkandclient=ubuntu>

QUESTION 7

What does the output of the command "svc_diag list --basic" show?

- A. Failover status
- B. Master_appliance_ID
- C. License status
- D. Boot mode

Correct Answer: B

QUESTION 8

DRAG DROP

Order the steps to prepare for an NDU process.

Select and Place:

| | |
|---|--------|
| Deploy using PowerStore Manager or RestAPI | Step 1 |
| Validate PUHC passes | Step 2 |
| Download OE upgrade package from the support site | Step 3 |
| Validate host multipathing is configured | Step 4 |

Correct Answer:

| |
|--|
| |
| |
| |
| |

- Download OE upgrade package from the support site
- Validate host multipathing is configured
- Validate PUHC passes
- Deploy using PowerStore Manager or RestAPI

QUESTION 9

Which Dell EMC PowerStore network uses an appliance backplane?

- A. ICD
- B. MPIO
- C. Inter-node
- D. Inter-cluster management

Correct Answer: C

Reference: <https://blocksandfiles.com/2020/05/05/dell-emc-powerstore-midrange-array-launch-analysis/>

QUESTION 10

How is a defective DIMM displayed in Dell EMC PowerStore Manager?

- A. Orange with an empty state
- B. Blue with a faulted state
- C. Orange with a faulted state
- D. Blue with an empty state

Correct Answer: C

QUESTION 11

A Storage Administrator has an existing single appliance Dell EMC PowerStore 3000T cluster. An additional

PowerStore 9000T has been purchased to add into the existing cluster. How does the administrator proceed?

- A. Additional VLTi links on the ToR switching must be configured for the 9000T to support the increased inter-switch network load
- B. Add the new 9000T appliance into the cluster per the procedure; mixed models of the same type are supported
- C. Remove two of the four NVMe NVRAM drives from the 9000T the caching configuration of all clustered appliances must match
- D. The new appliance cannot be added to the cluster; appliance model and type must match when clustering appliances together

Correct Answer: A

QUESTION 12

What is the reason for the best practice of leaving 2 Us of space at the bottom of the rack when racking Dell EMC PowerStore systems?

- A. Provide better rack stability
- B. Provide cooling air intake
- C. Leave room for serviceability
- D. Leave room for serviceability

Correct Answer: C

Leave 2U at the bottom of the rack for serviceability.

Reference: <https://www.dell.com/support/manuals/en-pk/powerstore-5000/pwrstr-plang/rack-space-guidelines?guid=guid-2a17a9ef-a0f6-4e49-943d-a7513cf682a8&lang=en-us>

QUESTION 13

Through which network do external hosts connect to the cluster for data access?

- A. Management
- B. ICM
- C. ICD
- D. Storage

Correct Answer: D

Reference: https://topics-cdn.dell.com/pdf/pwrstr-hcg_en-us.pdf

QUESTION 14

Refer to the exhibit.

```
#(conf-range-eth1/1/55-1/1/56) vlt-domain 1
#(conf-vlt-1) discovery-interface ethernet 1/1/55-1/1/56
#(conf-vlt-1) backup destination 172.17.57.30
```

What is the result of the network configuration shown for a Dell EMC PowerStore T?

- A. Interfaces are configured for remote replication traffic
- B. Interfaces are configured for PowerStore discovery traffic
- C. Ports 1/1/55 and 1/1/56 are added to a new LACP domain
- D. Ports 1/1/55 and 1/1/56 are added to the VLTi domain

Correct Answer: B

QUESTION 15

What describes the ICM and ICD networks?

- A. Address type is dynamic and automatically reconfigured on discovery results
- B. They are NOT encrypted
- C. Address type is persistent throughout the life of the cluster and CANNOT to be modified
- D. They are encrypted with IPsec

Correct Answer: D

[DES-1241 PDF Dumps](#)

[DES-1241 Practice Test](#)

[DES-1241 Study Guide](#)