

E20-351^{Q&As}

Storage Attached Network (SAN) Specialist Exam

Pass EMC E20-351 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/e20-351.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



QUESTION 1

What are the device special files naming convention in an HP-UX environment?

- A. `././PHYSICALDRIVE#`
- B. Block Device is `/dev/dsk/c##t##d#` and Character Device is `/dev/rdisk/c##t##d#`
- C. Block Device is `/dev/dsk/c##t##d#s2` and Character Device is `/dev/rdisk/c##t##d#s2`
- D. Block Device is `/dev/hdisk#` and Character Device is `/dev/rhdisk#`

Correct Answer: B

QUESTION 2

The Fibre Channel standard defines a layer protocol. Which level serves as the transport layer?

- A. FC-1
- B. FC-2
- C. FC-3
- D. FC-4

Correct Answer: D

QUESTION 3

Your customer is managing a B-Series switch with Web Tools. You are in the discovery phase of a new implementation and need the switch zoning and configuration information. How can this information be retrieved from Web Tools as part of a single report?

- A. Click the Admin radio button and then click "view report"
- B. Click the Info radio button, choose to download report as html or text.
- C. Click the Status radio button, choose to download report as html or text when prompted
- D. Click the Status radio button, log in and click "view report"

Correct Answer: A

QUESTION 4

What is the default initial setup user that installs and sets up the Symmetrix Management Console environment?

- A. eccadmin

B. emcadmin

C. smc

D. smcadmin

Correct Answer: C

QUESTION 5

On EMC Control Center, what are the two methods used to discover B-Series switches and directors?

A. Brocades Connectivity Access Layer and SMI Provider

B. Brocades Fabric Access Layer and SMI Provider

C. Brocades Fabric Access Layer and SNMP Provider

D. DSM Connect and SMI Provider

Correct Answer: B

QUESTION 6

Which layer in the iSCSI protocol stack contains the command descriptor blocks between the initiator and target?

A. IP

B. iSCSI

C. SCSI

D. TCP

Correct Answer: C

QUESTION 7

FashionStar Inc. is implementing an SRDF over IP solution. It wants to use a pair of MP-1620 switches to allow FC data to transfer over its existing network, and does not want to merge its fabrics. Which technology will FashionStar be using?

A. FCIP

B. iFCP

C. iSATA

D. iSCSI

Correct Answer: B

QUESTION 8

In a switched fabric environment, what happens when a N_Port is connected to a F_Port?

- A. The fabric login begins associating the physical address and the network MACaddress.
- B. The fabric login begins associating the physical address and the NAA
- C. The fabric login begins associating the physical address and the World Wide Name.
- D. The fabric login begins associating the World Wide Name and the frame address.

Correct Answer: C

QUESTION 9

What is the port configuration when implementing multiprotocol routing for B-Series FCIP?

- A. E_Port
- B. F_Port
- C. FL_Port
- D. VE_Port

Correct Answer: D

QUESTION 10

In Control Center, imported zones are copied to which folder?

- A. Active Zones
- B. Inactive Zones
- C. Modified Zones
- D. Planned Zones

Correct Answer: D

QUESTION 11

How many bits are in a Fibre Channel address?

- A. 16
- B. 24

C. 64

D. 128

Correct Answer: B

QUESTION 12

Click the Exhibit button. In the exhibit, network communication flow is represented by the red arrows. Which type of communication is this known as? ** Exhibit Missing **

A. Full-duplex communication

B. Half-duplex communication

C. Multiple point communication protocol (MPCP)

D. Standard Ethernet communication protocol (SECP)

Correct Answer: A

QUESTION 13

Which ASIC can be found in an M-Series switch?

A. Bloom

B. Skyline

C. Tuscany

D. Viper

Correct Answer: D

QUESTION 14

For which operating systems are the Common Serial Number (C) bit set on a Symmetrix FA port?

A. Used for Heterogeneous FA Port Sharing/IBM AI with FC 6227, 6228, 6239/VMware

B. Used for Solaris only

C. Used for Windows/Solaris/AIX

D. Used for Windows/Solaris/HP-UX

Correct Answer: D

QUESTION 15

Which bits contain the Area Address in a Fabric Channel address?

- A. First set of 8 bits
- B. Fourth set of 8 bits
- C. Second set of 8 bits
- D. Third set of 8 bits

Correct Answer: C

[Latest E20-351 Dumps](#)

[E20-351 PDF Dumps](#)

[E20-351 Braindumps](#)