

E20-377^{Q&As}

RecoverPoint/SE Specialist Exam for Implementation Engineers

Pass EMC E20-377 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/e20-377.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which two TimeFinder/Clone actions are initiated when issuing a Symclone establish command?

- A. Create and Terminate
- B. Re-create and Terminate
- C. Create and Activate
- D. Activate and Restore

Correct Answer: A

QUESTION 2

What state should the BCV be in for it to be accessed by a host?

- A. restored state
- B. synchronized state
- C. copy on first access state
- D. split state

Correct Answer: D

QUESTION 3

Which feature allows the contents of a BCV to remain unchanged during and after operation? Even while the BCV and the standard is synchronized?

- A. Protected restore
- B. Full establish
- C. Symmir restore
- D. Incremental restore

Correct Answer: C

QUESTION 4

You have been asked to create a configuration for a single engine Symmetric V-Max array with 8 DAEs and 64 drivers. They would like to have the data devices with RAID 5(7+1) protection. What would be the largest number of members you would recommend for a stripped metavolume?

- A. 4
- B. 16
- C. 8
- D. 32

Correct Answer: B

QUESTION 5

A storage administrator wants to know, what is the maximum number of non-differential TimeFinder/Clone copies they can create against a standard source device?

- A. 16
- B. 15
- C. 32
- D. 8

Correct Answer: A

QUESTION 6

Which Solutions Enabler daemon provides for centralized gatekeeper device management for all applications requiring access to Symmetrix arrays?

- A. Base daemon (storapid)
- B. GNS daemon (storgnsd)
- C. RDF daemon (storrdfd)
- D. Event daemon (storevntd)

Correct Answer: A

QUESTION 7

Which document should a EMC customer consult if there are questions about a system design during an SRDF/A engagement?

- A. Configuration Guide
- B. Level of Effort
- C. Practitioner's Guide

D. Scope Document

Correct Answer: A

QUESTION 8

With the DMX-3 and DMX4, where is the VCM database stored?

A. Symmetrix Logical Volume

B. Symmetrix File System

C. Symmetrix Virtual Device

D. Symmetrix VCM Device

Correct Answer: B

QUESTION 9

How does TimeFinder emulation mode convert commands?

A. Mirror commands are converted to Clone commands

B. Snap commands are converted to Mirror commands

C. Mirror commands are converted to Snap commands

D. Clone commands are converted to Mirror commands

Correct Answer: B

QUESTION 10

In symmetric V-max series array running Enginuity 5874, which device is used as a pass-through device for Auto provisioning?

A. VDEV

B. VCM

C. ACLX

D. SFS

Correct Answer: C

QUESTION 11

In a single-hop SRDF/AR setup the options have been set as follows: Cycle Time=300 Delay Time=0 Overflow=Next The symreplicate session was started at time 0. The actual cycle time was 450 seconds. How many seconds after the start of the first cycle will the next cycle start?

- A. 600
- B. 300
- C. 450
- D. 900

Correct Answer: A

QUESTION 12

On the Symmetrix platform, which type of RAID protection ensures the best random write performance?

- A. RAID 1
- B. RAID S
- C. RAID 6
- D. RAID 5

Correct Answer: A

QUESTION 13

Open Replicator Cold Push will be used to move data between a Symmetrix V-Max array and a third-party array. Which step is required before issuing the Open Replicator create command?

- A. Set the control devices to Not Ready
- B. Set the remote devices to Not Ready
- C. Set the control devices to Read Write
- D. Set a device reservation on the remote devices

Correct Answer: A

QUESTION 14

What is recommended before creating a TimeFinder/Clone replica?

- A. Ensure that the clone target devices are not being actively accessed
- B. Ensure that the production application using the source devices is shut down

- C. Set the clone target devices to a Not Ready state
- D. Ensure that all writes from the production application using the source devices are paused

Correct Answer: A

QUESTION 15

The necessary infrastructure is in place for application restart at a remote site. What is the primary impact to the customer of a single-hop SRDF/AR solution compared to SRDF/S?

- A. Increased RTO with SRDF/S
- B. Increased RPO with SRDF/AR
- C. Increased number of links with SRDF/AR
- D. Decreased network bandwidth is needed with SRDF/S

Correct Answer: B

[E20-377 PDF Dumps](#)

[E20-377 VCE Dumps](#)

[E20-377 Exam Questions](#)